

ASUS WS X299 PRO Intel® X299 LGA 2066 (Socket R4) ATX

Brand : ASUS


Product code: 90SW0090-M0EAY0

Product name : WS X299 PRO

- 5-Way Optimisation: One-click, system-wide tuning, delivers optimised overclocking and intelligent cooling for a diverse range of workloads
 - Industry-leading cooling options: Comprehensive controls for fans and water pumps, via Fan Xpert 4 software or the acclaimed ASUS UEFI
 - Ultra-efficient VRM heatsink: Metal fin array connected to large surface area via a heatpipe tames X299 thermals to enable unthrottled performance
 - Next-gen transfer speeds: Up to 32Gbps dual M.2 and U.2, plus up to 10Gbps USB 3.1 Type-A and Type-C connections
- Intel X299, 2x Intel I210-AT, USB 3.1, Gigabit Ethernet, SATA 3, TPM, ATX



Processor		Rear panel I/O ports	
Processor manufacturer *	Intel	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4
Processor socket *	LGA 2066 (Socket R4)	USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity *	1
Processor number of cores supported	4, 6	USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity *	1
Memory		Ethernet LAN (RJ-45) ports *	2
Supported memory types *	DDR4-SDRAM	Network	
Number of memory slots *	8	Ethernet LAN	✓
Non-ECC	✓	Ethernet interface type	Gigabit Ethernet
Supported memory clock speeds	2133,2400,2600,3600,4133 MHz	LAN controller	Intel® I210-AT
Maximum internal memory *	128 GB	Features	
Storage controllers		Motherboard chipset *	Intel® X299
Supported storage drive interfaces *	SATA III	Component for *	Workstation
Graphics		Motherboard form factor *	ATX
Parallel processing technology support *	3-Way CrossFireX, 3-Way SLI	Motherboard chipset family *	Intel
Discrete graphics support	✓	Harmonized System (HS) code	84733020
Internal I/O		BIOS	
USB 2.0 connectors *	1	Clear CMOS button	✓
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Processor special features	
USB 3.2 Gen 2 (3.1 Gen 2) connectors *	1	Intel® Optane™ Memory Ready	✓
Number of SATA III connectors *	6	Weight & dimensions	
ATX Power connector (24-pin)	✓	Width	305 mm
CPU fan connector	✓	Depth	244 mm
Number of COM connectors	1	Height	291 mm
TPM connector	✓	Other features	
Rear panel I/O ports		PCI Express x4 (Gen 3.x) slots	1
USB 2.0 ports quantity *	4	Supported DIMM module capacities	16GB
		Weight	2.29 kg
		Number of DIMM slots	8



4712900810271



0889349810279



889349810279

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.