StarTech.com Dual Monitor USB C Docking Station with 60W Power Delivery for Windows Laptops - USB C to HDMI / DVI Dock -USB 3.1 Gen 1 Type C Dock w/ Charging - Thunderbolt 3 Compatible

Brand : StarTech.com

Product code: MST30C2HHPDU



Product name : Dual Monitor USB C Docking Station with 60W Power Delivery for Windows Laptops - USB C to HDMI / DVI Dock - USB 3.1 Gen 1 Type C Dock w/ Charging -Thunderbolt 3 Compatible

StarTech.com Dual Monitor USB C Docking Station with 60W Power Delivery for Windows Laptops - USB C to HDMI / DVI Dock - USB 3.1 Gen 1 Type C Dock w/ Charging - Thunderbolt 3 Compatible (MST30C2HHPDU)

StarTech.com Dual Monitor USB C Docking Station with 60W Power Delivery for Windows Laptops - USB C to HDMI / DVI Dock - USB 3.1 Gen 1 Type C Dock w/ Charging - Thunderbolt 3 Compatible. Connectivity technology: Wired, Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, USB Power Delivery up to: 60 W. Ethernet LAN data rates: 10,100,1000 Mbit/s, Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Product colour: Black, Silver, Data transfer rate: 5 Gbit/s, Maximum digital resolution: 4096 x 2160 pixels. Power source type: AC, AC input voltage: 100 - 240 V, Input current: 1.5 A. Windows operating systems supported: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10...



Ports & interfaces		Power	
Connectivity technology *	Wired	Compatible power plug types	EU. UK
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C		20, 01
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity USB Power Delivery USB Power Delivery revision USB Power Delivery up to HDMI ports quantity * Combo headphone/mic port Headphone outputs * Headphone connectivity	4 1 ✓ 2.0 60 W 2 ✓ 1 3.5 mm	Software Windows operating systems	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7, Windows 7 Enterprise, Windows 7, Windows 7 Home Basic x64, Windows 7 Home Premium, X64, Windows 7 Professional x64, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Network		supported	
Ethernet LAN * Ethernet LAN (RJ-45) ports Ethernet LAN data rates Networking standards Auto MDI/MDI-X Full duplex Performance	✓ 1 10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE 802.3u ✓		
Card reader integrated * X Data transfer rate 5 Gbit/s Maximum digital resolution 4096 x 2160 Product colour * Black, Silver Plug and Play ✓	×	Operational conditions	
	4096 x 2160 pixels	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	5 - 35 °C -40 - 70 °C 5 - 95%
UASP support	▼ √	Sustainability	
Housing material	Plastic	Sustainability compliance	✓
Power		Sustainability certificates	CE, RoHS
Power source type	AC	Weight & dimensions	
AC input voltage	100 - 240 V	Width	80 mm

Publication date: 20-JAN-2023. Prints or copies of Information are only valid on the printed Publication date

Power		Weight & dimensions	
Input current Output voltage Output current	ge 20 V	Depth Height Weight	220 mm 24 mm 259 g
Power consumption (typical) Power plug type	100 W	Packaging data	
	Type N	Package width Package depth Package height Package weight	157 mm 267 mm 90 mm 1.5 kg
		Packaging content	
		Cables included AC adapter included Quick start guide	USB Type-C ✔ ✔
		Technical details	

Harmonized System (HS) code

Products per master (outer) case

Master (outer) case width

Master (outer) case length

Master (outer) case height

Logistics data

Other features

Chipset

84733020

6 pc(s)


287 mm

337 mm

304 mm

- TPS65983

VIA/VLI - VL813, MegaChips -STDP4320, Realtek - RTL8153, C-Media - CM6533, Texas Instruments





065030872690

0065030872690

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.