

Gigabyte P650B power supply unit 650 W 20+4 pin ATX ATX Black

Brand : Gigabyte

Product code: 28200-P650B-1EUR

Product name : P650B

650W, 100-240 Vac, 50-60 Hz, Active PFC, 120mm

[Gigabyte P650B power supply unit 650 W 20+4 pin ATX ATX Black:](#)

80 Plus Bronze Certified

80 Plus certified ensures the better power efficiency. Less power waste reduces the heat and fan noise. P650B can be up to 89% efficiency.

Reliable Mesh Braided Cable

P650B provides the best solution for the system builds. The mesh braided cable reduces the clutter and improves the airflow in the case.

100% Japanese Capacitors

All capacitors are high quality Japanese capacitors, to produce the efficient performance and to ensure the longer reliability.

Single +12V Rail

Single +12V rail provides the best power output, stability and compatibility for the hardware. And it is the best design for installation.

120mm Hydraulic Bearing (HYB) Fan

120mm Hydraulic Bearing fan optimizes the noise reduction and the thermal performance. The fan speed is adjusted according to the automatic power detection. The Hydraulic Bearing fan provides longer and more stable life time.

Power		Ports & interfaces	
Total power *	650 W	PCI Express power connectors (6+2 pin)	4
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	50 - 60 Hz	ATX Power connector (24-pin)	✓
Input current	9, 4 A	Floppy disk drive connector	✓
Power Factor Correction (PFC) type	Active	PCI Express connector	✓
Combined power (+3.3V)	108 W	Performance	
Combined power (+12V)	648 W	80 PLUS certification *	80 PLUS Bronze
Combined power (+5V)	108 W	Purpose *	PC
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	12.5 W	ATX version	2.31
Max output current (+3.3V)	18 A	Mean time between failures (MTBF)	100000 h
Max output current (+12V)	0.3 A	Certification	CE/CCC/BSMI/KCC/EAC/UL/TUV/RCM/FCC/PSE
Max output current (+5V)	15 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	2.5 A	Fan diameter	12 cm
Efficiency	85%	Number of fans	1 fan(s)
Power protection features	Over power, Over voltage, Overcharge, Short circuit, Under voltage	Fan location	Top
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	140 mm
Number of SATA power connectors	6	Depth	150 mm
Peripheral (Molex) power connectors (4-pin) *	3	Height	86 mm
		Logistics data	
		Harmonized System (HS) code	84733020





4719331550295

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-MAR-2023. Prints or copies of Information are only valid on the printed Publication date