



## Lindy 1U 12 Way IEC Sockets, Horizontal PDU with IEC Mains Cable

**Brand :** Lindy

**Product code:** 29995

**Product name :** 1U 12 Way IEC Sockets, Horizontal PDU with IEC Mains Cable

1U 12 Way Horizontal Mount PDU, IEC C14 Male Plug to 12 x IEC Mains Sockets - Switched, 3m

[Lindy 1U 12 Way IEC Sockets, Horizontal PDU with IEC Mains Cable:](#)

- IEC 10A C14 Male Plug to 12 x IEC Sockets (total load must not exceed 10A)
- 10 Amp fuse built into the PDU
- Integral On/Off rocker switch
- A packet of fixing screws, cage nuts and washers supplied
- Cable Length: 3m
- Colour: RAL 7044 (Grey)

Lindy 1U 12 Way IEC Sockets, Horizontal PDU with IEC Mains Cable. Rack capacity: 1U, Type: Three-phase, Mounting: Horizontal. AC outlets quantity: 12 AC outlet(s), AC outlet types: C14 coupler. LED indicators: Power. Cable length: 3 m, Certification: BS5733. Management platform: IEC. Nominal input voltage: 250 V, Maximum current: 10 A, AC input frequency: 50 - 60 Hz



| Design                |                 | Features                |            |
|-----------------------|-----------------|-------------------------|------------|
| Type                  | Three-phase     | Cable length            | 3 m        |
| Rack capacity *       | 1U              | Certification           | BS5733     |
| Mounting              | Horizontal      | Management features     |            |
| Product colour        | Black           | Management platform     | IEC        |
| On/off switch         | ✓               | Power                   |            |
| Ports & interfaces    |                 | Nominal input voltage * | 250 V      |
| AC outlets quantity * | 12 AC outlet(s) | AC input frequency      | 50 - 60 Hz |
| AC outlet types *     | C14 coupler     | Maximum current *       | 10 A       |
| Output connections    | 12              | Maximum power           | 2500 W     |
| Features              |                 | Weight & dimensions     |            |
| LED indicators        | Power           | Height                  | 44.4 mm    |
| Surge protection      | ✓               | Packaging content       |            |
|                       |                 | Manual                  | ✓          |



4002888299954

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-OCT-2023. Prints or copies of Information are only valid on the printed Publication date