



## Origin Storage Inception TLC830 Pro Series 256GB M.2 (NGFF) 80mm SATA 3D TLC SSD

**Brand :** Origin Storage

**Product code:** OTLC2563DM.2/80



**Product name :** Inception TLC830 Pro Series 256GB M.2 (NGFF) 80mm SATA 3D TLC SSD

- Read Intensive, Mobile/Desktop Based, Professional Solutions
  - Does not invalidate OEM warranty
  - 100% compatible replacement/upgrade for storage solutions
  - Pre- & Post-Sale UK Based Tech Support
- Inception TLC830 Pro Series 256GB M.2 (NGFF) 80mm SATA 3D TLC SSD

Origin Storage Inception TLC830 Pro Series 256GB M.2 (NGFF) 80mm SATA 3D TLC SSD:



The Inception TLC830 Pro range of SSD Solutions are manufactured by Origin using the highest quality Tier 1 NAND and the latest generation of controllers which enables us to provide both high performance and strong reliability. All of our Inception SSDs come with 3 years advanced replacement warranty alongside free, in-house pre and post sales technical support. We can supply the TLC830 Pro in form factors of 2.5", 3.5" & M.2 with either SATA or NVME interfaces, whilst being available in a range of capacities designed to increase the performance & extend the lifecycle of any laptop or desktop.

Features		Power	
SSD form factor *	M.2	Operating voltage	3.3 V
SSD capacity *	256 GB	Power consumption (read)	2.78 W
Interface *	Serial ATA III	Power consumption (write)	4.28 W
Memory type *	3D TLC	Power consumption (idle)	0.5 W
NVMe *	✗	<b>Operational conditions</b>	
Component for *	PC/notebook	Operating temperature (T-T)	0 - 70 °C
Hardware encryption *	✗	Storage temperature (T-T)	-45 - 105 °C
Data transfer rate	6 Gbit/s	Operating relative humidity (H-H)	5 - 98%
Read speed	550 MB/s	Storage relative humidity (H-H)	5 - 98%
Write speed	500 MB/s	Operating vibration	16 G
Random read (4KB)	53760 IOPS	Operating shock	1500 G
Random write (4KB)	56320 IOPS	Maximum operating altitude	120000 m
Access time	0.2 ms	<b>Technical details</b>	
S.M.A.R.T. support	✓	Sustainability certificates	RoHS
ECC	✓	<b>Weight &amp; dimensions</b>	
Hot-swap	✗	Weight	7 g
Low-density parity-check (LDPC)	✓	<b>Packaging data</b>	
Mean time between failures (MTBF)	1000000 h	Storage drive adapter included	✗
Windows operating systems supported	✓	Screws included	✗
Linux operating systems supported	✓	Package type	Blister
TBW rating	100	<b>Logistics data</b>	
Compatible products	Universal	Harmonized System (HS) code	84717070



5056006150435

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.