

APC SMC1500I-2UC uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 900 W 4 AC outlet(s)




Brand : APC Product code: SMC1500I-2UC

Product name : SMC1500I-2UC



1.5 kVA, 900W, 170-300V, 50/60Hz, 459J, 432x477x86mm, 28.64kg, Black APC SMC1500I-2UC. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 900 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 477 mm, Height: 86 mm

Features		Battery	
UPS topology * Output power capacity * Output power *	Line-Interactive 1.5 kVA 900 W	Hot-swap battery Automatic battery test Cold start	√ √ √
Waveform *	Sine	Design	
Input operation voltage (max) * 300 Input frequency * 500 Output operation voltage (min) 220 Output operation voltage (max) 240	170 V 300 V 50/60 Hz 220 V 240 V 50/60 Hz ✓ 459 J	Form factor * Rack capacity Product colour * Display type LED indicators Certification	Rackmount 2U Black LCD ✓ C-tick, CE, CSA, GOST, UL 1778, VDE
Surge energy rating		Operational conditions	
Output voltage Total Harmonic Distortion (THD) Noise level Audible alarm(s) Web-based management Audible alarm modes	5% 46 dB	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Auto-restart	1	Technical details	
Temperature voltage compensation	1	Harmonized System (HS) code	85078000
Ports & interfaces		• • •	03070000
AC outlet types Power plug AC outlets quantity USB port USB 2.0 ports quantity Serial interface Serial interface type	C13 coupler C14 coupler 4 AC outlet(s)	Weight & dimensions Width Depth Height Weight Package width Package depth Package height	432 mm 477 mm 86 mm 28.6 kg 594 mm 603 mm 251 mm
Battery		Package weight	31.9 kg
Battery technology Battery life (max) Battery recharge time	Sealed Lead Acid (VRLA) 6 year(s) 3 h	Packaging data	31.3 kg
		Rack mount kit Cables included Quick installation guide Resource CD Software CD Logistics data	✓ USB cable ✓ ✓
		Products per pallet	16 pc(s)





731304332954

0731304332954

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.