APC

APC SMT1500IC uninterruptible power supply (UPS) Line-Interactive 1.5 kVA 1000 W 8 AC outlet(s)

Brand : APC   **Product code:** SMT1500IC

Product name : SMT1500IC

1.5 kVA, 1 kW, 151-302V, 50/60Hz, 459J, 171x439x219mm, 24.09kg, Black
APC SMT1500IC. UPS topology: Line-Interactive, Output power capacity: 1.5 kVA, Output power: 1000 W.
AC outlet types: C13 coupler, IEC Jumpers, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s).
Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h.
Form factor: Mini Tower, Product colour: Black, Cable length: 1.83 m. Width: 171 mm, Depth: 439 mm,
Height: 219 mm

Features

UPS topology *	Line-Interactive
Output power capacity *	1.5 kVA
Output power *	1000 W
Waveform *	Sine
Input operation voltage (min) *	151 V
Input operation voltage (max) *	302 V
Input frequency *	50/60 Hz
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	✓
Surge energy rating	459 J
Output voltage Total Harmonic Distortion (THD)	5%
Noise level	45 dB
Surge protection	✓
Audible alarm(s)	✓
Web-based management	✓
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	✓
Temperature voltage compensation	✓

Ports & interfaces

AC outlet types	C13 coupler, IEC Jumpers
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
USB port	✓
USB 2.0 ports quantity	1
Serial interface	✓
Serial interface type	RS-232
Serial ports quantity	1

Battery

Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	✓
Automatic battery test	✓
Cold start	✓

Design

Form factor *	Mini Tower
Cable length	1.83 m
Product colour *	Black
Display type	LCD
LED indicators	✓
Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Technical details

Harmonized System (HS) code	85078000

Weight & dimensions

Width	171 mm
Depth	439 mm
Height	219 mm
Weight	24.1 kg
Package width	328 mm
Package depth	595 mm

Ports & interfaces		Weight & dimensions	
Ethernet LAN (RJ-45) ports	1	Package height	376 mm
SmartSlot	✔	Package weight	27.2 kg
Battery		**Packaging data**	
Battery technology	Sealed Lead Acid (VRLA)	Cables included	RS-232, USB cable
		Quick installation guide	✔
		Resource CD	✔
		Software CD	✔
		Logistics data	
		Products per pallet	12 pc(s)

0731304332992

731304332992