



APC SMT1000RMI2UC uninterruptible power supply (UPS) Line-Interactive 1 kVA 700 W 4 AC outlet(s)



Brand : APC

Product code: SMT1000RMI2UC

Product name : SMT1000RMI2UC

Smart-UPS, Line Interactive, 1000VA, Rackmount 2U, 230V, 4x IEC C13 outlets, SmartConnect Port+SmartSlot, AVR, LCD

APC SMT1000RMI2UC. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 700 W. AC outlet types: C13 coupler, AC outlets quantity: 4 AC outlet(s), USB port type: USB Type-A. Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 477 mm, Height: 86 mm

Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	1 kVA	Automatic battery test	✓
Output power *	700 W	Cold start	✓
Waveform *	Sine	Replacement battery cartridge	APCRBC132
Input operation voltage (min) *	151 V	Design	
Input operation voltage (max) *	302 V	Form factor *	Rackmount
Input frequency *	50/60 Hz	Rack capacity	2U
Output operation voltage (min)	220 V	Product colour *	Black
Output operation voltage (max)	240 V	Display type	LCD
Output frequency	50/60 Hz	LED indicators	✓
Automatic Voltage Regulation (AVR)	✓	Certification	EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH
Surge energy rating	459 J	Operational conditions	
Response time	10 ms	Operating temperature (T-T)	0 - 40 °C
Output voltage Total Harmonic Distortion (THD)	5%	Storage temperature (T-T)	-15 - 45 °C
Noise level	45 dB	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Web-based management	✓	Operating altitude	0 - 3000 m
Auto-restart	✓	Non-operating altitude	0 - 15000 m
Temperature voltage compensation	✓	Technical details	
Ports & interfaces		Sustainability certificates	Green Premium, RoHS
AC outlet types	C13 coupler	Weight & dimensions	
AC outlets quantity	4 AC outlet(s)	Width	432 mm
USB port	✓	Depth	477 mm
USB port type	USB Type-A	Height	86 mm
Serial interface	✓	Weight	22.5 kg
Serial interface type	RJ-45	Package width	594 mm
Ethernet LAN (RJ-45) ports	1	Package depth	603 mm
SmartSlot	✓	Package height	251 mm
Battery		Package weight	31.4 kg
Battery technology	Sealed Lead Acid (VRLA)	Packaging data	
Number of batteries supported	1	Rack mount kit	✓
Battery life (max)	6 year(s)	Cables included	RS-232, USB cable
Battery recharge time	3 h	Quick installation guide	✓
		Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	8 pc(s)
		Harmonized System (HS) code	85078000



0731304332985



731304332985

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-MAR-2024. Prints or copies of Information are only valid on the printed Publication date