

APC SMC1000IC uninterruptible power supply (UPS) Line-Interactive 1 kVA 600 W 8 AC outlet(s)

Brand : APC Product code: SMC1000IC

Product name: SMC1000IC


1 kVA, 600W, 170-300V, 50/60Hz, 455J, 171x439x219mm, 17.27kg, Black APC SMC1000lC. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 600 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Mini Tower, Product colour: Black, Display type: LCD. Width: 171 mm, Depth: 439 mm, Height: 219 mm





Features		Battery	
UPS topology * Output power capacity * Output power * Waveform * Input operation voltage (min) * Input operation voltage (max) * Input frequency * Output operation voltage (min) Output operation voltage (max) Output frequency	Line-Interactive 1 kVA 600 W Sine 170 V 300 V 50/60 Hz 220 V 240 V 50/60 Hz	Battery life (max) Battery recharge time Hot-swap battery Automatic battery test Cold start Design Form factor * Product colour * Display type LED indicators	5 year(s) 3 h ✓ ✓ Mini Tower Black LCD ✓
Automatic Voltage Regulation (AVR) Surge energy rating	√ 455 J	Certification Operational conditions	CE, CSA, GOST, UL 1778, VDE
Output voltage Total Harmonic Distortion (THD) Noise level Surge protection Audible alarm(s) Web-based management Audible alarm modes Auto-restart Temperature voltage compensation	5% 41 dB	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Technical details Harmonized System (HS) code	0 - 40 °C -15 - 45 °C 0 - 95% 0 - 95% 0 - 3000 m 0 - 15000 m
Ports & interfaces		Weight & dimensions	
AC outlet types Power plug AC outlets quantity USB port USB 2.0 ports quantity	C13 coupler C14 coupler 8 AC outlet(s) 1	Width Depth Height Weight Package width	171 mm 439 mm 219 mm 17.3 kg 328 mm
Serial ports quantity Ethernet LAN (RJ-45) ports	1 1	Package depth Package height	595 mm 376 mm

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package weight	19.6 kg
		Packaging data	
		Cables included	USB cable
		Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	18 pc(s)





731304332947

0731304332947

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.