

## Epson TM-H6000V-213 180 x 180 DPI Wired & Wireless Dot matrix POS printer

**Brand :** Epson

**Product code:** C31CG62213

**Product name :** TM-H6000V-213



- Integrated point-of-sale printer: Capable of receipt printing, slip printing and cheque processing
- Boost efficiency: Fast prints speeds up to 350mm/s<sup>1</sup>, cheque processing and auto-cutter
- Flexible connectivity: Built-in USB and Ethernet in all models
- An investment for the future: ePOS-Print, ePOS-display and NFC
- Great value: Low total cost of ownership

180 x 180DPI, 350mm/sec, NFC, USB 1.1, USB 2.0, Ethernet, Serial, White

Epson TM-H6000V-213. Print technology: Dot matrix, Type: POS printer, Maximum resolution: 180 x 180 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 80 mm, Maximum paper size (slip): 230 x 297 mm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B, Serial interface type: RS-232. Sound pressure level (printing): 55 dB, Sound pressure level (standby): 55 dB, Mean time between failures (MTBF): 180000 h. Product colour: White

Printing		Features	
Colour	✘	Certification	CE, EN55024, EN55032 Class A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, Directive 2014/30/EU
Maximum resolution	180 x 180 DPI		
Print speed	5.7 lps	Design	Product colour * White
Print speed	350 mm/sec		
Print speed (receipt)	350 mm/sec	Power	AC input voltage 24 V
Character size	1.24 x 3.11 mm		
Character density	17.8 cpi	Operational conditions	Operating temperature (T-T) 5 - 45 °C Storage temperature (T-T) -10 - 50 °C Operating relative humidity (H-H) 10 - 90% Storage relative humidity (H-H) 10 - 90%
Printing characters	Text, Graphic, Barcode		
Character sets	ANK	System requirements	Pre-installed software Server Direct Print, ePOS-Display, ePOS-Print
Print technology *	Dot matrix		
Type *	POS printer	Weight & dimensions	Width 186 mm Depth 278 mm Height 181 mm Weight 4.4 kg
<b>Paper handling</b>			
Maximum roll diameter	8.3 cm	Packaging data	Quantity per pack 1 pc(s) Package width 294 mm Package depth 382 mm Package height 292 mm Package weight 5.67 kg
Supported paper width	80 mm		
Maximum paper size (slip)	230 x 297 mm	Packaging content	AC adapter included ✓
<b>Ports &amp; interfaces</b>			
USB port *	✓	Print technology	Column capacity 45 cps / 60 cps
USB connector	USB Type-A / USB Type-B		
Serial interface *	✓	Logistics data	Harmonized System (HS) code 84433210 Products per pallet 56 pc(s)
Serial interface type	RS-232		
Connectivity technology *	Wired & Wireless		
Near Field Communication (NFC)	✓		
Standard interfaces	Ethernet, NFC, RS-232, USB 1.1, USB 2.0		
<b>Network</b>			
Ethernet LAN *	✓		
<b>Features</b>			
Sound pressure level (printing)	55 dB		
Sound pressure level (standby)	55 dB		
Mean time between failures (MTBF)	180000 h		
Cutter	✓		
Half-cutter	✓		
Autocutter durability	3 million cuts		
Built-in MICR	✓		
Paper save function	✓		
Print head life	200 km		
Country of origin	China		

Features		Logistics data	
Maximum number of copies (slip)	3 copies	Products per pallet layer	8 pc(s)
Printer receipt unit life	20000000 lines	Pallet gross width	80 cm
Printer slip unit life	27000000 lines	Pallet gross length	120 cm
Ribbon life (slip)	4 million characters	Pallet gross height	2.18 m
Built-in sensors details	Middle of Paper pass sensor, Front cover open sensor, Roll paper cover open sensor, Paper End Sensor, Top of Form sensor, Bottom of Form sensor, Slip eject sensor, Receipt near-end sensor	Products per pallet (UK)	70 pc(s)
		Products per pallet layer (UK)	10 pc(s)
		Pallet width (UK)	100 cm
		Pallet length (UK)	120 cm
		Pallet height (UK)	2.18 m
Technical details			
		Font size	1.41 mm (W) x 3.39 mm (H) / 0.99 mm (W) x 2.4 mm (H)
		Changeable interface	✓
Other features			
		Buffer size	4 KB
		Mean cycles between failures (MCBF)	65000000
		Print head life	200000000 million characters



8715946651132

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-FEB-2024. Prints or copies of Information are only valid on the printed Publication date