## Lindy 1m High Speed HDMI Cable, Black Line

Brand : Lindy

Product code: 36471

Product name : 1m High Speed HDMI Cable, Black Line

- Entry level High Speed HDMI 2.0 cable for home and small office applications
- Supports UHD resolutions up to 4096x2160@60Hz 4:4:4 8bit
- Robust PVC housing, nickel connectors, gold flashed contacts
- Triple shielded cable, corrosion resistant copper coated steel 30AWG conductors
- HDMI 2.0 compliant: 3D, 4K, 18Gbps, HEC, ARC, CEC, Dolby® True HD, DTS-HD Master Audio; HDMI
- ATC certified; 10 year warranty

1m High Speed HDMI Cable, Black Line

Lindy 1m High Speed HDMI Cable, Black Line. Cable length: 1 m, Connector 1: HDMI Type A (Standard), Connector 1 gender: Male, Connector 2: HDMI Type A (Standard), Connector 2 gender: Male, Connector contacts plating: Gold, HDMI version: 2.0, Maximum resolution: 4096 x 2160 pixels, Data transfer rate: 18 Gbit/s, Audio Return Channel (ARC), Product colour: Black





#### Features

### Cable length \* Connector 1 \* Connector 2 \* Connector 1 gender \* Connector 2 gender \* Connector 1 form factor Connector 2 form factor Product colour \* HDMI version Supported graphics resolutions Audio Return Channel (ARC) HDMI Ethernet channel Data transfer rate Maximum resolution AWG wire size Contact material Connector contacts plating \* Connector housing material Connector material Cable material

### 1 m HDMI Type A (Standard) HDMI Type A (Standard) Male Male Straight Straight Black 2.0 4096 x 2160 1 1 18 Gbit/s 4096 x 2160 pixels 30 Phosphor bronze Gold Polyvinyl chloride (PVC) Nickel Copper

Features	
Cable type	Round cable
Cable jacket material	Polyvinyl chloride (PVC)
Shield material	Aluminium
Bending radius (min)	6 cm
Colour depth	8 bit
Colour sampling	4:4:4
Nominal attenuation	300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB, 2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB
Certification	RoHS, REACH, UL
Quantity per pack *	1 pc(s)
Operational conditions	
Operating temperature (T-T)	-10 - 80 °C
Storage temperature (T-T)	-10 - 80 °C
Weight & dimensions	
Cable diameter	6 mm
Connector 1 dimensions (WxDxH)	19.2 x 34.1 x 10.6 mm
Connector 2 dimensions (WxDxH)	19.2 x 34.1 x 10.6 mm
Package type	Polybag
Logistics data	
Harmonized System (HS) code	84733080



# 4002888364713

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.