



Lindy DisplayPort 1.2 to HDMI 2.0 18G Active Converter

Brand : Lindy

Product code: 41068

Product name : DisplayPort 1.2 to HDMI 2.0 18G Active Converter

DisplayPort 1.2 to HDMI 18G Active Converter

[Lindy DisplayPort 1.2 to HDMI 2.0 18G Active Converter:](#)

Connects a DisplayPort source to an HDMI 4k display or projector
Supports resolutions up to 3840x2160@60Hz
Audio pass-through if supported by the video source
Active chipset for enhanced compatibility with various graphic cards
2 year warranty

The Lindy DisplayPort to HDMI Converter connects a DisplayPort source device to an HDMI display or projector. It supports full 4K Ultra HD resolutions up to 3840x2160@60Hz 4:4:4 8bit and HDMI 2.0 with up to 18Gbps bandwidth, making it the ideal tool for high-resolution tasks like editing 4K videos.

HDCP 2.2 ensures issue-free playback of a variety of 4K Ultra HD movies, TV shows and other 4K content as well as existing Full HD signals.

Active conversion guarantees compatibility with various graphics cards including AMD Eyefinity, NVIDIA surround and Intel Collage, great for an immersive gaming setup or a productive multi-screen working experience.



Features		Operational conditions	
Connector 1 form factor	Straight	Operating temperature (T-T)	0 - 70 °C
Connector 2 form factor	Straight	Storage temperature (T-T)	-20 - 70 °C
Connector contacts plating	Gold	Operating relative humidity (H-H)	10 - 90%
Cable length *	1.5 m	Storage relative humidity (H-H)	10 - 90%
Connector 1 *	DisplayPort	Sustainability	
Connector 2 *	HDMI Type A (Standard)	Sustainability certificates	RoHS
Connector 1 gender *	Male	Weight & dimensions	
Connector 2 gender *	Female	Cable diameter	5 mm
HDMI version	2.0a	Connector 1 dimensions (WxDxH)	31.5 x 20 x 9 mm
HDCP	✓	Connector 2 dimensions (WxDxH)	45 x 45 x 15 mm
HDCP version	2.2	Weight	20 g
DisplayPort version	1.2	Packaging data	
Maximum resolution	3840 x 2160 pixels	Quantity per pack	1 pc(s)
Supported video modes	2160p	Package width	160 mm
Data transfer rate	18 Gbit/s	Package depth	160 mm
Bend radius (min)	5.5 cm	Package height	20 mm
Product colour	Black	Package type	Polybag
Chipset	PS176	Package weight	45 g
Jacket material	Polyvinyl chloride (PVC)	Technical details	
Connector housing material	Thermoplastic elastomer (TPE)	Harmonized System (HS) code	84733080
Colour depth	8 bit		
Colour sampling	4:4:4		
Converter type	Active video converter		
Certification	CE, UKCA, FCC, RoHS, REACH		



4002888410687

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.