



APC Smart-UPS 2200VA uninterruptible power supply (UPS) Line-Interactive 2.2 kVA 1980 W 9 AC outlet(s)

Brand : APC

Product code: SMT2200IC

Product name : Smart-UPS 2200VA

Smart-UPS, Line Interactive, 2200VA, Tower, 230V, 8x IEC C13+2x IEC C19 outlets, SmartConnect Port+SmartSlot, AVR, LCD

APC Smart-UPS 2200VA. UPS topology: Line-Interactive, Output power capacity: 2.2 kVA, Output power: 1980 W. AC outlets quantity: 9 AC outlet(s), USB port type: USB Type-A. Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 8.7 min, Typical backup time at half load: 25 min. Product colour: Black, Display type: LCD, Certification: CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE. Width: 197 mm, Depth: 544 mm, Height: 435 mm



Features		Battery	
UPS topology *	Line-Interactive	Typical backup time at half load	25 min
Output power capacity *	2.2 kVA	Battery life (max)	5 year(s)
Output power *	1980 W	Battery recharge time	3 h
Waveform *	Sine	Design	
Input operation voltage (min) *	151 V	Product colour *	Black
Input operation voltage (max) *	302 V	Display type	LCD
Input frequency *	50/60 Hz	LED indicators	✓
Output operation voltage (min)	220 V	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE
Output operation voltage (max)	240 V	Operational conditions	
Surge energy rating	365 J	Operating temperature (T-T)	0 - 40 °C
Response time	6 ms	Storage temperature (T-T)	-15 - 45 °C
Emergency Power Off (EPO)	✓	Operating relative humidity (H-H)	0 - 95%
Output voltage Total Harmonic Distortion (THD)	5%	Storage relative humidity (H-H)	0 - 95%
Noise level	45 dB	Operating altitude	0 - 3000 m
Power protection features	Over voltage, Overload	Non-operating altitude	0 - 15000 m
Audible alarm(s)	✓	Technical details	
Audible alarm modes	Alarm when on battery, Low battery alarm, Battery replacement	Sustainability certificates	Green Premium, RoHS
Auto-restart	✓	Weight & dimensions	
Ports & interfaces		Width	197 mm
AC outlets quantity	9 AC outlet(s)	Depth	544 mm
USB port	✓	Height	435 mm
USB 2.0 ports quantity	1	Weight	48.8 kg
USB port type	USB Type-A	Package width	381 mm
Serial interface	✓	Package depth	762 mm
Serial ports quantity	1	Package height	699 mm
Ethernet LAN (RJ-45) ports	1	Package weight	61.9 kg
SmartSlot	✓		

Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Cables included	RS-232, USB cable
Typical backup time at full load	8.7 min	Software CD	✓
Logistics data			
		Products per pallet	9 pc(s)
		Harmonized System (HS) code	85078000



0731304337317



731304337317

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 07-MAY-2024. Prints or copies of Information are only valid on the printed Publication date