



APC SMT3000RMI2UC uninterruptible power supply (UPS) Line-Interactive 3 kVA 2700 W 9 AC outlet(s)

Brand : APC

Product code: SMT3000RMI2UC

Product name : SMT3000RMI2UC



- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, Rack mounting hardware, Rack Mounting support rails, USB cable

2.7 kW, 3 k VA, 50/60Hz, 200 V, 6ms, RJ-45 Serial, SmartSlot, USB, 320 Joules

APC SMT3000RMI2UC. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W. AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 547 VAh, Typical backup time at full load: 3.2 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 480 mm, Depth: 683 mm, Height: 86 mm



Features		Battery	
UPS topology *	Line-Interactive	Automatic battery test	✓
Output power capacity *	3 kVA	Cold start	✓
Output power *	2700 W	Design	
Waveform *	Sine	Form factor *	Rackmount
Input operation voltage (min) *	151 V	Rack capacity	2U
Input operation voltage (max) *	302 V	Cable length	2 m
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	LED indicators	Status
Automatic Voltage Regulation (AVR)	✓	Certification	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE, REACH, PEP, EOL
Surge energy rating	320 J	Operational conditions	
Hold time (min)	4 ms	Operating temperature (T-T)	0 - 40 °C
Hold time (max)	8 ms	Storage temperature (T-T)	-15 - 45 °C
Efficiency	98.9%	Operating relative humidity (H-H)	0 - 95%
Noise level	55 dB	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3000 m
Auto-restart	✓	Non-operating altitude	0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler, C19 coupler	Sustainability certificates	RoHS
Power plug	C20 coupler	Harmonized System (HS) code	85078000
AC outlets quantity	9 AC outlet(s)	Weight & dimensions	
Number of output IEC jumpers	3	Width	480 mm
USB port	✓	Depth	683 mm
Serial interface	✓	Height	86 mm
Serial interface type	RJ-45	Weight	44.3 kg
Ethernet LAN (RJ-45) ports	1	Package width	600 mm
SmartSlot	✓		

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package depth	980 mm
Battery capacity	547 VAh	Package height	254 mm
Typical backup time at full load	3.2 min	Package weight	51.7 kg
Typical backup time at half load	11.5 min	Packaging data	
Battery life (max)	5 year(s)	Rack mount kit	✓
Battery recharge time	3 h	Cables included	RS-232, USB cable
Hot-swap battery	✓	Quick installation guide	✓
		Software CD	✓
		Bundled software	Powershute Business Edition
		Other features	
		Nominal output voltage	230 V
		Nominal input voltage	230 V



0731304337348



731304337348



5706998907233

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.