

Lindy 7.5m USB 2.0 Type A to B Cable, Anthra Line

Brand: Lindy Product code: 36676

Product name: 7.5m USB 2.0 Type A to B Cable, Anthra

Line

- Professional choice USB 2.0 Type A to B cable for commercial and high performance AV and IT installations
- Supports data transfer speeds up to 480Mbps
- Robust PVC housing, nickel connectors and gold plated contacts
- Double shielded cable, corrosion resistant tinned copper conductors
- USB 2.0, 480Mbps; 10 year warranty


7.5m USB 2.0 Type A to B Cable, Anthra Line

Lindy 7.5m USB 2.0 Type A to B Cable, Anthra Line. Cable length: 7.5 m, Connector 1: USB A, Connector 2: USB B, USB version: USB 2.0, Maximum data transfer rate: 480 Mbit/s, Connector contacts plating: Nickel, Product colour: Black





Features		Features	
Cable length * 7.5 m USB version * USB 2.0 Connector 1 * USB A Connector 2 * USB B Connector 1 gender * Male Connector 2 gender * Male Connector 1 form factor Straight	Product colour * Cable type Nominal attenuation Certification Weight & dimensions Cable diameter Bend radius (min)	Black Round cable 5.8db/km RoHS, REACH, UL 5 mm 1.6 cm	
Connector 2 form factor AWG wire size Connector material Contact material	WG wire size connector material contact material connector contacts plating able jacket material conductor material connector shielding connector shield material connector housing material connector housing material connector shield material connector housing material connector shield material connector housing material connector shield material connector housing material connector housing material connector shield material connector housing material connector shield material connector housing material connector shield material connector housing material connector housing material	Connector 1 dimensions (WxDxH) 15.5 x 35 x 7.8 mm Connector 2 dimensions (WxDxH) 11.8 x 35 x 10.2 mm Packaging data	
Connector contacts plating Cable jacket material Conductor material		Quantity per pack * Package type Operational conditions	1 pc(s) Polybag
Connector shielding Connector shield material Connector housing material Maximum data transfer rate		Operating temperature (T-T) Storage temperature (T-T) Logistics data Harmonized System (HS) code	0 - 60 °C 0 - 60 °C 84733080



4002888366762

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.