



## APC SMT750IC uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 500 W 6 AC outlet(s)

Brand : APC

Product code: SMT750IC

Product name : SMT750IC

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, USB cable

500 W, 750 VA, 50/60 Hz, 220 V, 6ms, SmartSlot, USB, 540 Joules

APC SMT750IC. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W.

AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery

technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 4.6 min, Typical backup time at

half load: 15.8 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Width: 138 mm,

Depth: 358 mm, Height: 157 mm



Features		Battery	
UPS topology *	Line-Interactive	Cold start	✓
Output power capacity *	0.75 kVA	<b>Design</b>	
Output power *	500 W	Form factor *	Tower
Waveform *	Sine	Cable length	1.83 m
Input operation voltage (min) *	151 V	Product colour *	Black
Input operation voltage (max) *	302 V	Display type	LCD
Input frequency *	50/60 Hz	LED indicators	Status
Output operation voltage (min)	220 V	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH, PEP, EOLI
Output operation voltage (max)	240 V	<b>Operational conditions</b>	
Automatic Voltage Regulation (AVR)	✓	Operating temperature (T-T)	0 - 40 °C
Surge energy rating	540 J	Storage temperature (T-T)	-15 - 45 °C
Efficiency	98%	Operating relative humidity (H-H)	5 - 95%
Noise level	40 dB	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3000 m
Auto-restart	✓	Non-operating altitude	0 - 15000 m
<b>Ports &amp; interfaces</b>		<b>Technical details</b>	
AC outlet types	C13 coupler	Sustainability certificates	RoHS
Power plug	C14 coupler	Harmonized System (HS) code	85078000
AC outlets quantity	6 AC outlet(s)	<b>Weight &amp; dimensions</b>	
Number of output IEC jumpers	2	Width	138 mm
USB port	✓	Depth	358 mm
SmartSlot	✓	Height	157 mm
<b>Battery</b>		Weight	13.2 kg
Battery technology	Sealed Lead Acid (VRLA)	Package width	278 mm
Typical backup time at full load	4.6 min	Package depth	499 mm
Typical backup time at half load	15.8 min	Package height	301 mm
Battery life (max)	5 year(s)		
Battery recharge time	3 h		

Battery		Weight & dimensions	
Hot-swap battery	✓	Package weight	14.2 kg
Automatic battery test	✓	<b>Packaging data</b>	
		Cables included	USB cable
		Manual	✓
		Quick installation guide	✓
		Bundled software	Powershute Business Edition
		<b>Logistics data</b>	
		Products per pallet	24 pc(s)



0731304340317



731304340317

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.