



APC SMT750RM12UC uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 500 W 4 AC outlet(s)

Brand : APC

Product code: SMT750RM12UC

Product name : SMT750RM12UC



2U, 500 W, 750 VA, 230V, IEC-320 C14, 50/60Hz, RJ-45 Serial, SmartSlot, USB, 459Joules
APC SMT750RM12UC. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 168 VAh, Typical backup time at full load: 5.5 min. Form factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 406 mm, Height: 89 mm



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	0.75 kVA	Hot-swap battery	✓
Output power *	500 W	Automatic battery test	✓
Waveform *	Pure sine	Cold start	✓
Input operation voltage (min) *	151 V	Design	
Input operation voltage (max) *	302 V	Form factor *	Rackmount
Input frequency *	50/60 Hz	Rack capacity	2U
Output operation voltage (min)	220 V	Product colour *	Black
Output operation voltage (max)	240 V	LED indicators	Battery replacement
Automatic Voltage Regulation (AVR)	✓	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, TUV, UL 1778, VDE, REACH, PEP, EOLI
Surge energy rating	459 J	Operational conditions	
Hold time (max)	2 ms	Operating temperature (T-T)	0 - 40 °C
Efficiency	97.7%	Storage temperature (T-T)	-15 - 45 °C
Noise level	42 dB	Operating relative humidity (H-H)	0 - 95%
Surge protection	✓	Storage relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Operating altitude	0 - 3000 m
Auto-restart	✓	Non-operating altitude	0 - 15000 m
Ports & interfaces		Technical details	
AC outlet types	C13 coupler	Sustainability certificates	Green Premium, RoHS
Power plug	C14 coupler	Weight & dimensions	
AC outlets quantity	4 AC outlet(s)	Width	432 mm
Number of output IEC jumpers	2	Depth	406 mm
USB port	✓	Height	89 mm
Serial interface	✓	Weight	17.3 kg
Serial interface type	RJ-45	Package width	546 mm
SmartSlot	✓	Package depth	584 mm
Battery		Package height	241 mm
Battery technology	Sealed Lead Acid (VRLA)	Package weight	21.2 kg
Battery capacity	168 VAh		
Typical backup time at full load	5.5 min		
Typical backup time at half load	16 min		
Battery life (max)	5 year(s)		

Packaging data

Rack mount kit	✓
Cables included	RS-232, USB cable
Quick installation guide	✓
Software CD	✓

Logistics data

Products per pallet	16 pc(s)
Harmonized System (HS) code	85078000



0731304340324



731304340324

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-MAR-2024. Prints or copies of Information are only valid on the printed Publication date