

Lexmark MX722ade Laser A4 1200 x 1200 DPI 66 ppm

Brand : Lexmark

Product code: 25B0050

Product name : MX722ade

A4, Monochrome Laser, Duplex, 66ppm, 1200 x 1200DPI, CCD Scan, Gigabit Ethernet, USB 2.0 Type A/Type B

Lexmark MX722ade. Print technology: Laser, Printing: Mono printing, Maximum resolution: 1200 x 1200 DPI. Copying: Mono copying. Scanning: Colour scanning. Maximum ISO A-series paper size: A4. Direct printing. Product colour: Black, Grey



Printing		Network	
Print technology *	Laser	Ethernet LAN *	✓
Printing *	Mono printing	Cabling technology	10/100/1000Base-T(X)
Duplex printing *	✓	Ethernet LAN data rates	10,100,1000 Mbit/s
Maximum resolution *	1200 x 1200 DPI	Security algorithms	HTTPS, IPsec, LEAP, MD5, MSCHAPv2, PEAP, SNMP, SNMPv3, SSL/TLS, TTLS
Print speed (black, normal quality, A4/US Letter) *	66 ppm	Performance	
Duplex print speed (black, normal quality, A4/US Letter)	40 ppm	Maximum internal memory	6144 MB
Time to first page (black, normal)	4 s	Internal memory *	2048 MB
Copying		Built-in processor	✓
Duplex copying *	✓	Processor frequency	1200 MHz
Copying *	Mono copying	Processor cores	4
Copy speed (black, normal quality, A4)	66 cpm	Sound pressure level (printing)	57 dB
Time to first copy (black, normal)	4 s	Sound pressure level (duplex printing)	57 dB
Copier resize	25 - 400%	Sound pressure level (copying)	60 dB
Scanning		Sound pressure level (scanning)	56 dB
Duplex scanning *	✓	Design	
Scanning *	Colour scanning	Product colour *	Black, Grey
Optical scanning resolution (black)	600 x 600 ppi	Market positioning *	Business
Optical scanning resolution (colour)	600 x 600 ppi	Built-in display *	✓
Maximum scan area	215.9 x 355.8 mm	Display diagonal	17.8 cm (7")
Scanner type *	Flatbed & ADF scanner	Touchscreen	✓
Scan technology	CCD	Control type	Touch
Scan to	E-mail, FTP, PC, USB	Colour display	✓
Scan speed (colour)	75 ppm	Power	
Scan speed (black)	75 ppm	Power consumption (printing)	850 W
Duplex scan speed (colour)	150 ppm	Power consumption (copying)	890 W
Duplex scan speed (black)	150 ppm	Power consumption (scanning)	73 W
Image formats supported	JPEG, JPG, TIFF	Power consumption (ready)	42 W
Document formats supported	PDF, XPS	Power consumption (sleep)	2 W
Fax		Energy Star Typical Electricity Consumption (TEC)	3.3 kWh/week
Fax transmission speed	3 sec/page	System requirements	
Modem speed	33.6 Kbit/s	Windows operating systems supported	✓
Features		Linux operating systems supported	✓
Recommended duty cycle	5000 - 100000 pages per month	Operational conditions	
Maximum duty cycle *	350000 pages per month	Operating relative humidity (H-H)	8 - 80%
Page description languages	Microsoft XPS, PCL 5e, PCL 6, PDF 1.7, PPDS, PostScript 3	Operating temperature (T-T)	10 - 32 °C

Input & output capacity		Operational conditions	
Total number of input trays *	2	Operating altitude	0 - 2896 m
Total input capacity *	650 sheets	Certificates	
Total output capacity *	550 sheets	ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA/CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, MET-I, IEC 60825-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), CISPR 22 Class A, KCC, CCC, CECF, CEL, A-tick DoC, C-tick CoC, UL-AR, KC mark, UL GS mark, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel GISS	
Paper input type	Paper tray		
Maximum number of input trays	5		
Maximum input capacity	3300 sheets		
Maximum output capacity	550 sheets		
Paper handling			
Maximum ISO A-series paper size *	A4	Sustainability certificates	ENERGY STAR
Paper tray media types *	Card stock, Envelopes, Labels, Plain paper, Transparencies	Weight & dimensions	
Multi-purpose tray media types	Envelopes, Labels, Plain paper, Transparencies	Width	558.8 mm
ISO A-series sizes (A0...A9) *	A4, A5, A6	Depth	578.4 mm
Non-ISO print media sizes	Executive, Folio, Legal, Letter, Oficio, Statement, Universal	Height	739.1 mm
JIS B-series sizes (B0...B9)	B5	Weight	44.1 kg
Envelopes sizes	7 3/4, 9, 10, B5, C5, DL	Packaging content	
Paper tray media weight	60 - 176 g/m ²	Imaging unit included	✓
Ports & interfaces		Power cord included	✓
Standard interfaces	Ethernet, USB 2.0	Other features	
Direct printing *	✓	Finishing option	✗
USB port	✓	Software CD	✓
USB connector	USB Type-A / USB Type-B	Documentation CD	✓
Optional connectivity	Wireless LAN		



0734646676366



734646676366

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.