

Epson WorkForce DS-80W

Brand : Epson

Product family: WorkForce

Product code: B11B253402

Product name : WorkForce DS-80W



- Scan anywhere: Small, lightweight design
- USB cable or integrated battery power: Scan up to 300 pages between battery charges
- Fast scanning speeds: At up to four seconds per page (8.5ppm)
- Simplify your workload: Continuous scanning with automatic feed mode
- Includes a range of software: Document Capture Pro 2, Epson Scan 2.0 and TWAIN driver support

WorkForce DS-80W
Epson WorkForce DS-80W. Maximum scan size: 216 x 1828 mm, Optical scanning resolution: 600 x 600 DPI, Input colour depth: 48 bit. Scanner type: Handheld scanner, Product colour: White, Display: LCD. Sensor type: CIS, Daily duty cycle (max): 300 pages, Light source: ReadyScan LED. Auto document feeder (ADF) input capacity: 1 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), Paper tray media weight: 35 - 270 g/m²

| Scanning | | Network | |
|---|---|-----------------------------------|--|
| Maximum scan size * | 216 x 1828 mm | Wi-Fi | ✓ |
| Optical scanning resolution * | 600 x 600 DPI | System requirements | |
| Colour scanning | ✓ | Compatible operating systems | Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003, Windows Server 2008 (32/64 Bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows XP |
| Duplex scanning * | ✗ | | Windows operating systems supported |
| Input colour depth | 48 bit | Mac operating systems supported | Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks |
| Output colour depth | 24 bit | | Server operating systems supported |
| Input greyscale depth | 16 bit | Operational conditions | |
| Output greyscale depth | 8 bit | Operating temperature (T-T) | 5 - 35 °C |
| Output monochrome depth | 8 bit | Storage temperature (T-T) | -25 - 60 °C |
| Scan speed (b/w, low res, A4) | 4 sec/page | Operating relative humidity (H-H) | 10 - 85% |
| Scan speed (colour, low res, A4) | 4 sec/page | Storage relative humidity (H-H) | 10 - 90% |
| Design | | Weight & dimensions | |
| Scanner type * | Handheld scanner | Width | 272 mm |
| Product colour * | White | Depth | 47 mm |
| Display | LCD | Height | 34 mm |
| Colour display | ✗ | Weight | 300 g |
| Built-in display * | ✓ | Packaging content | |
| Performance | | Cables included | USB |
| Sensor type * | CIS | Bundled software | Document Capture Pro 2.0, Epson Scan 2 |
| Light source | ReadyScan LED | Other features | |
| Scan file formats | BMP, JPEG, PDF, PNG, TIFF | Output resolutions | 600 dpi |
| Daily duty cycle (max) * | 300 pages | Image formats supported | BMP, JPEG, TIFF, PNG |
| Scan drivers | TWAIN, WIA, SANE, ICA | | |
| Input capacity | | | |
| Auto document feeder (ADF) input capacity | 1 sheets | | |
| Paper handling | | | |
| Scanning media types supported | Business Card, Plastic Card, Post Card(JPN) | | |
| Maximum ISO A-series paper size * | A4 | | |
| Paper tray media weight | 35 - 270 g/m ² | | |
| Auto Document Feeder (ADF) media weight | 35 - 270 g/m ² | | |
| Ports & interfaces | | | |
| USB port * | ✓ | | |
| USB version | 2.0 | | |

| Ports & interfaces | | Technical details | |
|---------------------|-----------------------|--|-----------|
| Standard interfaces | USB 2.0, Wireless LAN | Master (outer) case GTIN (EAN/UPC) 8715946663005 | |
| Power | | Logistics data | |
| Power supply type * | USB | Products per pallet | 360 pc(s) |
| Packaging data | | Master (outer) case length | 360 mm |
| Quantity per pack | 1 pc(s) | Master (outer) case height | 320 mm |
| Package width | 141 mm | Master (outer) case width | 350 mm |
| Package depth | 330 mm | Pallet gross length | 120 cm |
| Package height | 67 mm | Pallet gross width | 80 cm |
| Package weight | 597 g | Pallet gross height | 171 cm |
| Features | | Products per master (outer) case | 10 pc(s) |
| Country of origin | China | Products per pallet layer | 60 pc(s) |
| | | Products per pallet layer (UK) | 60 pc(s) |
| | | Products per pallet (UK) | 360 pc(s) |
| | | Pallet length (UK) | 120 cm |
| | | Pallet width (UK) | 100 cm |
| | | Pallet height (UK) | 171 cm |
| | | Harmonized System (HS) code | 84716070 |



8715946662848

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.