

## Gigabyte Aorus P750W power supply unit 750 W 20+4 pin ATX ATX Black

**Brand :** Gigabyte

**Product code:** GP-AP750GM-UK

**Product name :** Aorus P750W

- Fully Modular Design
- High quality 100% Japanese Capacitors
- 135mm 2 ball bearing smart fan with fan stop function
- 80 PLUS Gold certified: above 90% efficiency at 50% load
- Single +12V rail
- OCP/OTP/OVP/OPP/UVP/SCP protection

Aorus P750W, ATX 12V v2.31, 750 W, 100-240 V, 47-63 Hz, 80Plus Gold, 150x160x86 mm

Gigabyte Aorus P750W. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 65 cm, Cabling type:

Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold.

Product colour: Black, Cooling type: Active, Fan diameter: 13.5 cm. Width: 150 mm, Depth: 160 mm,

Height: 86 mm



<b>Power</b>		<b>Ports &amp; interfaces</b>	
Total power *	750 W	PCI Express power connectors (6+2 pin)	4
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
AC input frequency	47 - 63 Hz	ATX power connector (20+4 pin)	✓
Input current	10 A	Floppy drive power connector	2
Power factor	0.9	Floppy disk drive connector	✓
Power Factor Correction (PFC) type	Active	PCI Express connector	✓
Combined power (+3.3V)	120 W	Cabling type	Modular
Combined power (+12V)	744 W	<b>Performance</b>	
Combined power (+5V)	120 W	80 PLUS certification *	80 PLUS Gold
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	20 A	ATX version	2.31
Max output current (+12V)	62 A	Bearing technology	Ball bearing
Max output current (+5V)	20 A	Mean time between failures (MTBF)	100000 h
Max output current (-12V)	0.3 A	<b>Design</b>	
Max output current (+5Vsb)	3 A	Product colour	Black
Hold time	16 ms	Cooling type	Active
Efficiency	90%	Fan diameter	13.5 cm
Power Good signal delay range	100 - 150 ms	Number of fans	1 fan(s)
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Fan location	Top
<b>Ports &amp; interfaces</b>		On/off switch	✓
Motherboard power connector *	20+4 pin ATX	<b>Weight &amp; dimensions</b>	
Motherboard power cable length	65 cm	Width	150 mm
Number of SATA power connectors	6	Depth	160 mm
Peripheral (Molex) power connectors (4-pin) *	5	Height	86 mm
		<b>Logistics data</b>	
		Harmonized System (HS) code	84733020



4719331551070

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-MAY-2023. Prints or copies of Information are only valid on the printed Publication date