PHILIPS

Philips P Line LCD monitor with USB-C Dock 329P9H/00

Brand : Philips Product family: P Line Product code: 329P9H/00

Product name : LCD monitor with USB-C Dock 329P9H/00

- P Line
- 32 (31.5"/80 cm diag.)
- 4K UHD (3840 x 2160)

Sync-on-green (SOG)

P Line LCD monitor with USB-C Dock

Philips P Line LCD monitor with USB-C Dock 329P9H/00:

When every detail matters, Philips Brilliance 32" 4K display delivers crisp visuals with accurate colour. Convenient features like USB-C docking and a secure pop-up webcam with Windows Hello increase your productivity.

Philips P Line LCD monitor with USB-C Dock 329P9H/00. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub. VESA mounting, Height adjustment. Product colour: Black











Display		Ergonomics	
Display diagonal *	80 cm (31.5")	Panel mounting interface	100 x 100 mm
Display resolution *	3840 x 2160 pixels	Cable lock slot *	✓
HD type *	4K Ultra HD	Cable lock slot type	Kensington
Native aspect ratio *	16:9	Height adjustment *	✓
Display technology *	LED	Height adjustment	18 cm
Panel type *	IPS	Pivot	✓
Backlight type	W-LED	Pivot angle	-90 - 90°
Touchscreen *	×	Swivelling	✓
Display brightness (typical)	350 cd/m²	Swivel angle range	-175 - 175°
Response time	5 ms	Tilt angle range	-5 - 25°
Anti-glare screen	✓	Picture-in-Picture	✓
Screen shape *	Flat	On Screen Display (OSD)	✓
Aspect ratio	16:9		Simplified Chinese, Traditional
Contrast ratio (typical) *	1300:1	On Screen Display (OSD) Janguages English, Spanish, Finn	Chinese, Czech, German, Dutch,
Contrast ratio (dynamic)	50000000:1		Greek, Hungarian, Italian, Japanese
Dynamic contrast ratio marketing name	SmartContrast		Korean, Polish, Portuguese, Russian Swedish, Turkish, Ukrainian
Maximum refresh rate *	60 Hz	Number of OSD languages	20
Viewing angle, horizontal	178°	Plug and Play	✓
Viewing angle, vertical	178°	LED indicators	Operation, Stand-by
Display number of colours *	1.07 billion colours	Tilt adjustment	✓
Pixel pitch	0.182 x 0.182 mm	Power	
Pixel density	140 ppi	Energy efficiency class (SDR) *	G
Horizontal scan range	30 - 160 kHz	Energy consumption (SDR) per 1000	
Vertical scan range	23 - 80 Hz	hours *	51 kWh
Viewable size, horizontal	69.7 cm	Power consumption (typical) *	33.95 W
Viewable size, vertical	39.2 cm	Power consumption (standby) *	0.5 W
Digital horizontal frequency	30 - 160 kHz	Power consumption (PowerSave)	30.8 W
Digital vertical frequency	23 - 80 Hz	AC input voltage	100 - 240 V

Deplay Septem Power P				
IDCCI VM Power supply type Infermal Infermal Surface Andreess 25% Energy efficiency scale A to G Surface Andreess 8AGB Operating temperature (17) 0.40°C Colour panul 90% Some of the participal pathwale burnship (14) 20-80°C MCRG coverage (typical) 90% Operating altitude 0-1219 m Adobe RC coverage (typical) 90% On-1219 m 0-1219 m Adobe RC coverage (typical) 4 Percent 0-1219 m Exported LPV sync 4 Scand included V Desploy 8KGR 4 Scand included V Port Coverage (typical) 4 Amount Search (15) Type Cto USB Type	Display		Power	
Haze rate 59% Energy efficiency scale A to G Colour space AGB Operation conditions 0 - 4 o ° C Colour space AGB Operating temperature (T-T) -20 - 60 ° C KNSC coverage (typical) 90% Operating alleture 0 - 80% AGOBE CRIS Coverage (typical) 90% Operating alleture 0 - 80% AGOBE CRIS Coverage (typical) X Packaging content Display SRGB Y Packaging content Professor X Manual Y Professor X Manual Y AMD FreeSync* X Manual Y	Display diagonal (metric)	80 cm	AC input frequency	50 - 60 Hz
Surface bandmesse 3H Operating stemperature (T-T) 0 - 40 °C Colour gamut 90% Operating stemperature (T-T) -0 - 60 °C ASBG coverage (typical) 90% Operating relative humidary (H-T) -20 - 60 °C MTSC coverage (typical) 90% Operating relative humidary (H-T) -20 - 60 °C Aschoe RGB coverage 3Y Operating relative humidary (H-T) -20 - 60 °C Separate HV sync Y Stand included JEST (M-T) Portormace X Stand included JEST (M-T) WORD AC SYNC * X August (M-T) JEST (M-T) AMD FreeSync * Separate sync, Sync-on-green Builded Software JEST (M-T) Component video sync Separate sync, Sync-on-green Weight & dimensor TEST mm Elscherfore text-honlogy / Weight & dimensor 75 mm Elscherfore text-honlogy / Weight & dimensor 75 mm Bull-in speakers * / Weight (without stand) 75 mm Bull-in speakers * 2 Weight (without stand) 75 mm	DDC/CI	✓	Power supply type	Internal
RGB colour space SRGB 90% Operating temperature (T-T) 20.60 °C 0 - 40 °C 0 - 60 °C	Haze rate	25%	Energy efficiency scale	A to G
RGB cloud repace 98CB Operating temperature (T-T) 0 - 40 °C 20 · 60 °C 30 °C <	Surface hardness	3H	Operational conditions	
Colour gamit (Vipical) 90% Scionge temperature (T-T) 20 - 60 °C Central partitive humidity (H-H) 20 - 60 °C 20 - 60 °C Non-coperating validation 0 - 3658 m Non-coperating validation 0 - 2458 m Non-copera	RGB colour space	sRGB	•	0 - 40 °C
Sikes George (typical) 108% Operating relative humidity (H+H) 20 - 80% 36%	Colour gamut	90%		
NIS. Coverage (processing) 90% Operating altitude 0 – 3658 m Abdobe RGB coverage 27 Packaging content Display AGB V Packaging content USA play AGB V Packaging content HDMD, DisplayPort, USB Type-C to U	sRGB coverage (typical)	108%		
ABOOD RAGIO CONTRICT Packaging content Separate I/V sync Packaging content Performance Cables included / HOM, DisplayPort, USB Type-C, US	NTSC coverage (typical)	90%		
Separate H/V sync	Adobe RGB coverage	87%		
Display SRGB	3D	×		0 12132 III
Performance Cables included HDM, Display/bort, USB Type-C to USB Type-C, USB Typ	Separate H/V sync	✓	Packaging content	
No No No No No No No No	Display sRGB	✓	Stand included	
NVDIA G-SYNC* X Manual √ √ AMD FreeSync* Searate sync, Sync-on-green (50G) Bundled software SmartControl Flicker-free technology √ Weight & dimensions Flicker-free technology √ Width (with stand) 246 mm Multimedia Jopeth (with stand) 636 mm Built-in speaker(s)* √ Weight (with stand) 715 mm Number of speakers 2 Depth (without stand) 715 mm Number of speakers 2 Depth (without stand) 715 mm RMS rated power 6 W Height (without stand) 715 mm Market positioning ** 4 Height (without stand) 715 mm Market positioning ** Home Package width 733 kg Postage Package width 793 mm Menter product color Feet colour Black Package height 673 mm Feet colour Black Package weight 14.4 kg Feet colour Black Package weight 14.5 kg Certification	Performance		Cables included	
AMD FreeSync* X Manual X Component video sync Separate sync, Sync-on-green Bundled software SmartControl Ficker-free technology V Width (with stand) 715 mm Muttered Height (with stand) 636 mm Built in speaker(s)* V Weight (with stand) 10.6 kg Built in speaker(s)* V Weight (with stand) 10.6 kg Built in speaker(s)* V Weight (with stand) 10.6 kg Built in speaker(s)* V Weight (without stand) 11 mm Number of speakers 2 Depth (without stand) 41 mm Number of speakers 2 Depth (without stand) 41 mm Megapixel (approx.) 2 MP Weight (without stand) 41 mm Megapixel (approx.) 4 Mp Weight (without stand) 41 mm Possign Home Package width 73 mm Built in speaker(s) Black Package width 136 mm Possign Heavy metal free Black Package width 14 kg <	NVIDIA G-SYNC *	×	Cables Included	
Componen video sync Spearare sync, Sync-on-green (SOG) Bundled software SmartControl Flicker-free technology 4 Weight & dimensions Low Bible Light technology 4 Width with sand) 246 mm Multimedia Height (with stand) 367 mm Bullt-in speaker(s)* 4 Weight (with stand) 10.6 kg Bullt-in camera 4 Weight (without stand) 71.5 mm Number of speakers 2 Depth (without stand) 21 mm Megapixel (approx) 2 MP Weight (without stand) 21 mm Megapixel (approx) 2 MP Package width 79.3 mm Marker positioning* Home Package width 793 mm Marker positioning* Black Package weight 14.4 kg Product colour* Black Package weight 14.4 kg Fore colour Black Package weight 14.4 kg Feet colour Black Package weight 14.4 kg Certification CERCILLS, TUY Engo, TUY/GS, SEMC Sustainability certificates New Yellow <			Manual	√
Extrapolation Extrapolatio				SmartControl
Multimedia	Component video sync			
Depth (with stand)	Flicker-free technology	✓	<u> </u>	715
Multimedia Height (with stand) 636 mm Bullt-in camera* 4 Weight (with stand) 10.6 kg Bullt-in camera* 4 Width (without stand) 715 mm Number of speakers 2 Depth (without stand) 51 mm MKS rated power 6 W Height (without stand) 41 mm Megapixel (approx.) 2 MP Weight (without stand) 7.33 kg Bullt-in microphone 7 Postage 733 mm Market postioning** Home Package width 793 mm Product colour** Black Package beight 166 mm Product colour** Black Package weight 14 kg Feet colour Black Package bye 673 mm Feet colour Black Package bye 14 kg Feet colour Keark, FCC Class B, China ROHS, CETLUS, TUV Ergo, TUV/GS, SEMKO, EPA Sustainability Weight (with stand) 70 cycle FR, Mercury Feet colour Kertilis, TUV Ergo, TUV/GS, SEMKO, EPA Recyclable material 85% Certification VERTILIS, TUV Ergo, TUV/GS, SE	Low Blue Light technology	✓	,	
Built-in papaker(s)* / Weight (with stand) 10.6 kg Built-in camera* / Worth (without stand) 51 mm Number of speakers 2 Depth (without stand) 51 mm RMS rated power 6 W Height (without stand) 412 mm Megapixel (approx.) 2 MP Weight (without stand) 412 mm Built-in microphone 7 Package Postgr 73 3 kg Package Market positioning* Home Package width 793 mm Product colour* Black Package weight 186 mm Foet colour Black Package weight 14.4 kg Feet colour Black Package weight 14.4 kg Feet colour Ela Mirk, FCC Class B, China RoHS, UKRAINIAN, ICES-003, CU-EAC, ETUS, TUV Ergo, TUV/GS, SEMKO, EPA Sustainability certificates ENERGY STAR, TCO, WEEE, RoHS Certification EPA VESTEUS, TUV Ergo, TUV/GS, SEMKO, EPA European Product Registry for Error part Package type PVC/BFR, Mercury EPA UKBA INAINIA, ICES-003, CU-EAC, EPA European Product Registry for Error part Package type	Multimedia		• •	=
Built-in camera* Very Width (without stand) 715 mm Number of speakers 2 Depth (without stand) 51 mm RMS rated power 6 W Height (without stand) 51 mm RMS rated power 6 W Height (without stand) 713 mm Mery Megapixel (approx.) 2 MP Weight (without stand) 733 kg Built- in microphone V Package depth 793 mm Market positioning* Home Package depth 186 mm Product colour* Black Package height 673 mm Feet colour Black Package weight 14.4 kg Feet colour Black Package weight 14.4 kg Feet colour Black Package weight 14.4 kg Ger Lius, TUV Foo, TUV/GS, SEMK (EPA CERL (EPA CLIUS TUV Foo, TUV/GS, SEMK (EPA CLIUS T	Built-in speaker(s) *	1		
Number of speakers 2 Depth (without stand) 51 mm RMS rated power 6 W Height (without stand) 412 mm Megapixel (approx.) 2 MP Weight (without stand) 412 mm Built-in microphone 7 MP Weight (without stand) 73 kg Built-in microphone 7 MP Packaging data Product colour* Black Package weight 136 mm Front bezel colour Black Package weight 673 mm Feet colour Black Package weight 673 mm Feet colour He (mercury) EMAIN, FCC Class B, China RoHS, UKRAINIAN, ICE\$-003, CU-EAC, CETLUS, TUV Ergo, TUV/SS, EMNO (EPAC, CETLUS, TUV Ergo, TUV/SS, EMNO (EPA	·			•
RNS rated power 6 W Height (without stand) 412 mm Megapixel (approx.) 2 MP Weight (without stand) 412 mm Built-in microphone 7 Packaging data Design Package width 733 mm Market positioning* Home Package depth 166 mm Frond to colour Black Package weight 673 mm Feet colour Black Package weight 14.4 kg Feet colour Ed Mark, FCC class B, China RoHS, ECC, CETLUS, TUX Fegro, TUX/SS, SEMX Sustainability certificates ENERGY STAR, TCO, WEEE, RoHS Certification CE. FCC class B, China RoHS, EAR Sustainability certificates ENERGY STAR, TCO, WEEE, RoHS Compilance industry standards CE. FCC class B, China RoHS, EAR European Product Registry for Energy Labelling (EPREL) code ENERGY STAR, TCO, WEEE, RoHS Ports & interfaces Recyclable material 85% Built-in USB hub* V Logstics dat USB Type-A downstream ports of upstream port type USB Type-A downstream ports 1 Certification Secuptability Secuptability Product S				
Megapixel (approx.) 2 MP Megapix (without stand) 7,33 kg Built-in microphone V Weight (without stand) 7,33 kg Design Package width 793 mm Market positioning * Home Package width 793 mm Product colour * Black Package beight 673 mm Front bezel colour Black Package weight 14.4 kg Feet colour Ede Colour Heavy metals free Hg (mercury) Sustainability VERIFY Certification CE Mark, FCC Class B, China RoHS, EFRU, TUV Ergo, TUV/GS, SEMKO, EPA Sustainability certificates ENERGY STAR, TCO, WEEE, RoHS Certification CE, FCC Class B, China RoHS, EFR European Product Registry or Product Registry or PVC/BFR, Mercury PVC/BFR, Mercury Certification CE, FCC Class B, China RoHS, EFR Error Recyclable material 85% Compliance industry standards V Logistics dat USB sustream port type USB Type-C DisplayOrd Alternate V Logistics dat USB Type-C DisplayOrd Alternate V Logistics dat S5285210 USB Type-C Displa	•			
Built-in microphone Packagin gdta Design Package width 793 mm Market positioning* Home Package height 186 mm Product colour* Black Package height 673 mm Front bezel colour Black Package weight 14.4 kg Feet colour Black Package weight 14.4 kg Heavy metals free Hg (mercury) CE Mark, FCC Class B, China ROHS, CE MAIN, ICES-003, CU-EAC, CETLUS, TUV Frgo, TUV/GS, SEMKO, EPA Sustainability Certification CE, FCC Class B, China ROHS, LUKRAINIAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMKO, EPA European Product Registry for European P	•			
Package width 793 mm Market positioning* Home Package depth 186 mm Product colour* Black Package height 673 mm Front bezel colour Black Package weight 14.4 kg Feet colour Black Package beight 14.4 kg Feet colour Black Package beight 14.4 kg Feet colour Black Package beight 14.4 kg Feet colour Black Package bype 80x Box Box Package bype 80x Box Box Package bype 80x Box Bull by Box Box Package bype 80x Certification CErC Class B, China RoHS, CERC List, TUV Ergo, TUV/GS, SEMKO, ECTLus, TUV Ergo, TUV/GS, SEMKO, EPA CETLus, TUV Ergo, TUV/GS, SEMK	= ' ''		weight (without stand)	7.33 kg
Market positioning* Home Package depth 195 mm Product colour* Black Package height 673 mm Front bezel colour Black Package height 14.4 kg Feet colour Black Package weight 14.4 kg Feet colour Black Package type Box Heavy metals free Hg (mercury) Sustainability Certification CE Mark, FCC Class B, China RoHS, EPA Sustainability ENERGY STAR, TCO, WEEE, RoHS Compliance industry standards CE, FCC Class B, China RoHS, EPA Sustainability certificates ENERGY STAR, TCO, WEEE, RoHS Built-in USB hub* V Buropean Product Registry for Energy Labelling (EPREL) code #13600 Built-in USB hub* V Logistics data #24 USB upstream port type USB Type-C Logistics data #252510 USB Type-A downstream ports 4 Ca adapter included V USB Type-C DisplayPort Alternate Mode V Ac adapter included V USB Power Delivery V V tuner integrated Y USB Pow	·	•	Packaging data	
Product colour * Black Package height 673 mm Front bezel colour Black Package weight 14.4 kg Feet colour Black Package type Box Heavy metals free Hg (mercury) Sustainability ENERGY STAR, TCO, WEEE, ROHS Certification CE Mark, FCC Class B, China RoHS, UKRAINIAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMO, EPA Sustainability certificates ENERGY STAR, TCO, WEEE, ROHS Compliance industry standards CE, FCC Class B, China RoHS, UKRAINIAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMO, EPA Recyclain data PVC/BFR, Mercury Posts & interfaces Fost-consumer recycled plastic 85% Post-consumer recycled plastic 85% USB type-A downstream ports quantity 1 Logistics data USB Type-C DisplayPort Alternate work A Cadapter included \$ USB Power Delivery Y A Cadapter included Y USB Power Delivery up to 65 W TV tuner integrated X USB Power Delivery up to 65 W Pricture-by-Picture (PbP) Y HDMI of squantity 2 Recommended resolution <t< td=""><td></td><td></td><td>Package width</td><td>793 mm</td></t<>			Package width	793 mm
Front bezel colour	· -		Package depth	186 mm
Feet colour Heavy metals free UKRAINJAN, ICES-003, CU-EAC, CETLus, TUV Ergo, TUV/GS, SEMCO, EPA CET, GETLUS, TUV Ergo, TUV/GS, SEMCO, EPA UKRAINJAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMCO, EPA UKRAINJAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMCO, EPA UKRAINJAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMCO, EPA UKRAINJAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMCO, EPA UKRAINJAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMCO, EPA Ports & interfaces Built-in USB hub* USB Type-A downstream port type USB Type-A downstream ports USB Type-A downstream ports USB Type-A downstream ports Quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to USB Power Delivery USB Power Delivery up to USB Power Delivery up to USB Power Delivery USB Power Delivery up to USB Power Delivery up to USB Power Delivery USB Power Delivery up to USB Power Delivery USB Power Delivery USB Power Delivery up to USB Power Delivery USB Power Delivery up to USB Power Delivery USB Power Delivery up to USB Power Delivery			Package height	673 mm
Heavy metals free Hg (mercury) CE Mark, FCC Class B, China RoHS, URKANINAM, ICES-003, CU-FAC, CETLus, TUV Ergo, TUV/GS, SEMKO, EPA COMPliance industry standards CE, FCC Class B, China RoHS, UKRANINAM, ICES-003, CU-FAC, CETLus, TUV Ergo, TUV/GS, SEMKO, EPA COMPliance industry standards CE, FCC Class B, China RoHS, UKRANINAM, ICES-003, CU-FAC, CETLus, TUV Ergo, TUV/GS, SEMKO, EPA Ports & interfaces Built-in USB Nub* VSB upstream port type USB Type-C USB Type-C USB Type-C DisplayPort Alternate Mode USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to USB Power Delivery up to USB Power Delivery USB Power Delivery up to USB Power Delivery USB P			Package weight	14.4 kg
CE Mark, FCC Class B, China RoHS, UKRAINIAN, ICES-003, CU-EAC, CETLus, TUV Fop, TUV/GS, SEMKO, EPA Compliance industry standards CE, FCC Class B, China RoHS, CE, FCC Class B, China RoHS, CE, FCC Class B, China RoHS, CETLus, TUV Ergo, TUV/GS, SEMKO, EPA COmpliance industry standards CETLUS, TUV Ergo, TUV/GS, SEMKO, EPA CE, FCC Class B, China RoHS, CETLus, TUV Ergo, TUV/GS, SEMKO, EPA Recyclable material Recyclable packaging material Recyclable pac			Package type	Box
Certification Likralinian, CLES-003, CU-EAC, CETLus, TUV Ergo, TUV/GS, SEMK DEPA CEDA C	Heavy metals free	-	Sustainability	
CETLUS, TUV Ergo, TUV/GS, SEMKO, EPA PORTS & INTERIOR SEMINAN, ICES-003, CU-EAC, CETLUS, TUV Ergo, TUV/GS, SEMKO, EPA Built-in USB hub* USB Type-C Number of upstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery			Sustainability certificates	ENERGY STAR TOO WEEE ROHS
EPA CE, FCC Class B, China RoHS, UKRAINIAN, ICES-003, CU-EAC, CETLus, TUV Ergo, TUV/GS, SEMKO, ETLus, TUV Ergo, TUV/GS, SEMKO, ETLus, TUV Ergo, TUV/GS, SEMKO, CETLus, TUV Ergo, TUV/GS, SEMKO, ETLus, TUV Ergo, TUV/GS, SEMKO, ETPA European Product Registry for Energy Labelling (EPREL) code Recyclable material Rec	Certification	cETLus, TUV Ergo, TUV/GS, SEMKO,	•	
CE, FCC Class B, China RoHS, UKRAINAN, LCES-003, CU-EAC, CETLus, TUV Ergo, TUV/GS, SEMKO, EPA Ports & interfaces Post-consumer recycled plastic Built-in USB hub* USB USB Type-C Number of upstream port type Number of upstream ports quantity USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to 65 W Potture-by-Picture (PbP) VICTURE enabled and type HDMI version DisplayPorts quantity 2 Companies DisplayPort squantity 2 Companies DisplayPort version				
Recycling data FAN Figh 100 Figh 200 Fi				413600
Ports & interfaces Bullt-in USB hub* USB Type-C Number of upstream ports ports Quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery up to DVI port HDMI orts quantity AC Accommended resolution BUMIN* HDMI ports quantity 2 Quantity AC Recommended resolution Bumin Recommended resolution Bumin Recommended Bumin Recommen	Compliance industry standards		Recycling data	
Ports & interfaces Post-consumer recycled plastic 85% Built-in USB hub * ✓ Logistics data USB upstream port type USB Type-C Harmonized System (HS) code 85285210 Number of upstream ports 1 Other features USB Type-A downstream ports quantity 4 AC adapter included ✓ USB Type-C DisplayPort Alternate Mode ✓ Notating X USB Power Delivery ✓ TV tuner integrated X USB Power Delivery up to 65 W Picture-by-Picture (PbP) ✓ DVI port X Recommended resolution 3840 x 2160 @ 60 Hz HDMI version 2.0 Recommended resolution 3840 x 2160 @ 60 Hz HDMI version 2.0 Recyclable packaging material 100% DisplayPorts quantity 2 MultiView PIP/PBP mode, 2 x devices DisplayPort version 1.2 Regulatory Approvals CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Headphone out * 4 PILITY Ergo; TUV/GS; SEMKO; EPA Headphone out buts 1 Delta E 2		5		050/
Built-in USB hub *	Ports & interfaces		•	
USB upstream port type Number of upstream ports 1 USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery up to Mode USB Power Delivery USB Power		./		8370
Number of upstream ports 1 USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery USB Power Delivery USB Power Delivery up to USB Power Delivery revision USB Power Delivery up to USB Power Delivery revision USB Power Delivery up to USB Power Delivery revision USB Power Delivery revision USB Power Delivery up to USB Power Deli			Logistics data	
USB Type-A downstream ports quantity USB Type-C DisplayPort Alternate Mode USB Power Delivery revision Mode USB Power Delivery revision Notating X V Usb Power Delivery revision Notating X V Usb Power Delivery revision Notating X V V turer integrated N V V textured Netured Notating X V Verture integrated N V V V V V V V V V V V V V V V V V V		**	Harmonized System (HS) code	85285210
quantity4AC adapter included✓USB Type-C DisplayPort Alternate Mode✓USB Power Delivery revision2.0USB Power Delivery✓RotatingXUSB Power Delivery up to65 WTV tuner integratedXUSB Power Delivery up to65 WPicture-by-Picture (PbP)✓DVI portXExterior finish typeTexturedHDMI *✓Recommended resolution3840 x 2160 @ 60 HzHDMI ports quantity2Picture enhancementSmartImageHDMI version2.0Recyclable packaging material100%DisplayPorts quantity2MultiViewPIP/PBP mode, 2 x devicesDisplayPort version1.2MultiViewPIP/PBP mode, 2 x devicesAudio inputXRegulatory ApprovalsCE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPAHeadphone out *YDelta E2	•		Other features	
USB Type-C DisplayPort Alternate Mode USB Power Delivery V TV tuner integrated X USB Power Delivery up to 65 W DVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPorts version DisplayPort version Audio input Headphone out * Headphone outputs HDCP USB Power Delivery revision Rotating TV tuner integrated X To tuner integrated X Textured Textured Recommended resolution 3840 x 2160 @ 60 Hz Ficture enhancement Recyclable packaging material MultiView PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Headphone outputs HDCP	71	4	AC adapter included	1
Mode USB Power Delivery USB Power Delivery up to USB Power Delivery up to OVI port HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio input Headphone out * Headphone out puts HDCP Rotating TV tuner integrated X HUture-by-Picture (PbP) Fexture of Inish type Textured 3840 x 2160 @ 60 Hz Picture enhancement SmartImage 100% Recyclable packaging material 100% PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Delta E V Delta E		1	•	
USB Power Delivery up to 65 W Picture-by-Picture (PbP) DVI port		·	•	
DVI port HDMI * HDMI ports quantity HDMI version DisplayPort version Audio input Headphone out * Headphone out y Headphone out puts HDCP Picture-by-Picture (PbP) Exterior finish type Recommended resolution Recommended resolution Recyclable packaging material MultiView PilyPBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Picture-by-Picture (PbP) Meximal publication in the sextendance of the properties of		•	-	
DVI port HDMI * HDMI ports quantity 2 HDMI version DisplayPorts quantity 2 Audio input Headphone out * Headphone out puts HDCP Exterior finish type Recommended resolution Recommended resolution Recommended resolution Recyclable packaging material MultiView Regulatory Approvals Exterior finish type Recommended resolution 3840 x 2160 @ 60 Hz SmartImage 100% PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA PIP/PBP mode, 2 x devices Delta E Delta E 2	• •		-	
HDMI ports quantity HDMI ports quantity 2 HDMI version DisplayPorts quantity 2 MultiView Picture enhancement Recyclable packaging material MultiView PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA HDCP Picture enhancement Recyclable packaging material MultiView PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Delta E 2	•		• • • • • • • • • • • • • • • • • • • •	
HDMI ports quantity HDMI version 2.0 Recyclable packaging material DisplayPorts quantity DisplayPort version Audio input Headphone out * Headphone out puts HDCP Picture enhancement Recyclable packaging material MultiView MultiView PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETILus; TUV Ergo; TUV/GS; SEMKO; EPA Delta E 2			• •	
HDMI version 2.0 DisplayPorts quantity 2 DisplayPort version 1.2 Audio input X Headphone out * Headphone out puts 1 HDCP Y Recyclable packaging material MultiView PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Delta E 2	• • •			
DisplayPorts quantity DisplayPort version 1.2 Audio input Headphone out * Headphone outputs HDCP PIP/PBP mode, 2 x devices CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; cETLus; TUV Ergo; TUV/GS; SEMKO; EPA Delta E 2				•
DisplayPort version Audio input Headphone out * Headphone outputs HDCP CE Mark; FCC Class B; China RoHS; UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Delta E 2				
Audio input Headphone out * Headphone outputs HDCP Regulatory Approvals UKRAINIAN; ICES-003; CU-EAC; CETLus; TUV Ergo; TUV/GS; SEMKO; EPA Delta E 2	• •			
Headphone outputs 1 HDCP Delta E 2 Light conserved.	•		Regulatory Approvals	UKRAINIAN; ICES-003; CU-EAC;
HDCP Delta E 2	·		3 · · · 3 · · · · · · · · · · · · · · ·	
Tiber	·		Delta F	
HDCP Version 2.2 Eight Sensor		•		
	HUCY Version	2.2		•

Network		Other features
Ethernet LAN	✓	EasyRead mode
Ergonomics		LowBlue mode ✓
VESA mounting *		Philips SmartUniformity 97 - 102%
	√	Mean time between failures (MTBF) 70000 h
		Ethernet LAN data rates 10,100,1000 Mbit/s
		Ethernet LAN (RJ-45) ports 1



8712581756826

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.