

HP Designjet T1600dr 36-in Printer

Brand : HP

Product family: Designjet

Product code: 3EK12A

Product name : DesignJet T1600dr 36-in Printer

- Print DesignJet T1600dr 36-in Printer

HP Designjet T1600dr 36-in Printer:

Keep the project momentum. With radically simple solutions and the easiest PDF printing^[1], it's easy for everyone to get great results every time. Meet deadlines with the fastest print speed in the most compact, quiet printer.^[2]

Dynamic security enabled printer Certain HP printers are intended to work only with cartridges that have a new or reused HP chip or electronic circuitry. These printers use dynamic security measures to block cartridges using a non-HP chip or electronic circuitry. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. Reused HP chips and electronic circuitry enable the use of reused, remanufactured, and refilled cartridges.








Printing		Performance	
Print technology *Thermal inkjetColour *Image: Colour *Maximum resolution *2400 x 1200 DPINumber of print cartridges *6Page description languages *HP-GL/2, HP-RTL, TIFF	Built-in display * Internal memory Internal storage capacity Storage media Sound power level (standby)	 131072 MB 500 GB HDD 32 dB 	
Printing colours *	Cyan, Grey, Magenta, Matte black, Photo black, Yellow	Power	
Print head Print speed (normal quality, A1)	1 universal printhead 180 pph	Power consumption (typical) Power consumption (off)	100 W 0.3 W
Copying		Operational conditions	
Copying * Scanning Scanning *	×	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	5 - 35 °C 20 - 80% -25 - 55 °C 0 - 90%
Paper handling		Sustainability	
Maximum print size * ISO A-series sizes (A0A9) Media thickness Maximum roll diameter	A0 (841 x 1189 mm) A0, A1, A2, A3 0.5 mm 14 cm	Sustainability certificates Weight & dimensions Width	ENERGY STAR 1390 mm
Ports & interfaces Wi-Fi *	* X het interface type Gigabit Ethernet het LAN * ort * X printing TCP/IP, BootP/DHCP (IPv4 only),	Depth Height Weight	760 mm 1080 mm 85 kg
Ethernet interface type Ethernet LAN *		Packaging data	
USB port * Direct printing Supported network protocols		Package width Package depth Package height Package weight	1477 mm 767 mm 800 mm 117 kg
Performance			
Product colour *	Black, White		





























194441078886

0194441078886

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.