



StarTech.com 1-port PCI Express RS232 Serial Adapter Card - PCIe RS232 Serial Host Controller Card - PCIe to Serial DB9 - 16950 UART - Low Profile Expansion Card - Windows & Linux

Brand : StarTech.com

Product code: PEX1S953LP

Product name : 1-port PCI Express RS232 Serial Adapter Card - PCIe RS232 Serial Host Controller Card - PCIe to Serial DB9 - 16950 UART - Low Profile Expansion Card - Windows & Linux

StarTech.com 1-port PCI Express RS232 Serial Adapter Card - PCIe RS232 Serial Host Controller Card - PCIe to Serial DB9 - 16950 UART - Low Profile Expansion Card - Windows & Linux (PEX1S953LP)
 StarTech.com 1-port PCI Express RS232 Serial Adapter Card - PCIe RS232 Serial Host Controller Card - PCIe to Serial DB9 - 16950 UART - Low Profile Expansion Card - Windows & Linux. Host interface: PCIe, Output interface: Serial, Expansion card standard: PCIe 1.1. Product colour: Green, Mean time between failures (MTBF): 277385 h. Chipset: Asix AX99100, Baud rate: 921.4 Kbit/s, FIFO (First In, First Out): 256 B. Windows operating systems supported: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10..., Server operating systems supported: Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows.... Width: 67 mm, Depth: 98 mm, Height: 150 mm



Ports & interfaces		System requirements	
Host interface *	PCIe	Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IoT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64
Output interface *	Serial		
Expansion card standard	PCIe 1.1		
Serial ports quantity	1		
Serial interface type	RS-232		
Peripheral (Molex) power connectors (4-pin)	1		
Design		Linux operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016
Internal *	✓		
Product colour	Green		
Mean time between failures (MTBF)	277385 h	Server operating systems supported	
Features			
Chipset	Asix AX99100	Linux operating systems supported	✓
Baud rate	921.4 Kbit/s		
FIFO (First In, First Out)	256 B	Server operating systems supported	
Data bits	5, 6, 7, 8, 9		
Stop bits	1, 1.5, 2	Linux operating systems supported	✓
Flow control support	✓		
Parity bit	Even, Mark, N, Odd, Space	Server operating systems supported	
Flow Control type	N, RTS/CTS, XON/XOFF		
Harmonized System (HS) code	84733020	Linux operating systems supported	✓
Operational conditions			
Operating temperature (T-T)	0 - 70 °C	Server operating systems supported	
Storage temperature (T-T)	-20 - 80 °C		
Operating relative humidity (H-H)	20 - 80%	Linux operating systems supported	✓
Technical details			
Sustainability compliance	✓	Server operating systems supported	
Sustainability certificates	CE, RoHS		
Weight & dimensions		Linux operating systems supported	✓
Width	67 mm		
Depth	98 mm		
Height	150 mm	Server operating systems supported	

Weight & dimensions

Weight	44 g
--------	------

Packaging data

Quantity	1
Mounting brackets included	✓
Manual	✓
Package width	142 mm
Package depth	170 mm
Package height	30 mm
Package weight	112 g

Logistics data

Products per master (outer) case	75 pc(s)
Master (outer) case width	360 mm
Master (outer) case length	685 mm
Master (outer) case height	315 mm



0065030881159



065030881159

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.