



APC SRT1500XLI uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1500 W

Brand : APC

Product code: SRT1500XLI

Product name : SRT1500XLI

1.5 kW, 1.5 kVA, 50/60Hz, 230V, 6x IEC 320 C13, 3:1, RJ-45 Serial, Smart-Slot, USB, 432 Joules
APC SRT1500XLI. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Rackmount/Tower, Product colour: Black, Cable length: 1.83 m. Width: 85 mm, Depth: 505 mm, Height: 432 mm



Features		Design	
UPS topology *	Double-conversion (Online)	Form factor *	Rackmount/Tower
Output power capacity *	1.5 kVA	Cable length	1.83 m
Output power *	1500 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	100 V	LED indicators	✓
Input operation voltage (max) *	275 V	International Protection (IP) code	IP20
Input frequency *	40/70 Hz	Certification	CE, EAC
Output operation voltage (min)	220 V	Operational conditions	
Output operation voltage (max)	240 V	Operating temperature (T-T)	0 - 40 °C
Output frequency	50/60 Hz	Storage temperature (T-T)	-20 - 50 °C
Surge energy rating	432 J	Operating relative humidity (H-H)	0 - 95%
Crest factor	3:1	Storage relative humidity (H-H)	0 - 95%
Emergency Power Off (EPO)	✓	Technical details	
Noise level	50 dB	Sustainability certificates	RoHS
Audible alarm(s)	✓	Harmonized System (HS) code	85078000
Ports & interfaces		Weight & dimensions	
USB port	✓	Width	85 mm
Serial interface	✓	Depth	505 mm
Serial interface type	RJ-45	Height	432 mm
SmartSlot	✓	Weight	20.5 kg
Battery		Package width	594 mm
Battery technology	Sealed Lead Acid (VRLA)	Package depth	749 mm
Battery life (max)	5 year(s)	Package height	246 mm
Battery recharge time	3 h	Package weight	29.6 kg
Hot-swap battery	✓	Packaging data	
		Manual	✓

Logistics data

Products per pallet 12 pc(s)



0731304340300



731304340300

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.