

APC SRT1500RMXLI-NC uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1500 W

Brand : APC Product code: SRT1500RMXLI-NC

Product name: SRT1500RMXLI-NC



1.5 kW, 1.5 kVA, 2U, 6x IEC 320 C13, 230V, 50/60Hz, 3:1, RJ-45 Serial, Smart-Slot, USB, 432 Joules APC SRT1500RMXLI-NC. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. Serial interface type: RJ-45. Battery technology: Sealed Lead Acid (VRLA), Battery voltage: 48 V, Battery life (max): 5 year(s). Form factor: Rackmount, Product colour: Black, Cable length: 1.83 m. Width: 432 mm, Depth: 505 mm, Height: 85 mm





Features		Design	
UPS topology * Double-conversion (Online) Output power capacity * 1.5 kVA Output power * 1500 W Waveform * Sine Input operation voltage (min) * 50 V Input operation voltage (max) * 150 V Input frequency * 40/70 Hz Output operation voltage (min) 220 V Output operation voltage (max) 240 V Output operation voltage (max) 240 V Output frequency 50/60 Hz Surge energy rating 432 J Crest factor 3:1 Emergency Power Off (EPO) Noise level 50 dB Audible alarm(s)	1.5 kVA 1500 W Sine 50 V 150 V 40/70 Hz	Form factor * Cable length Product colour * Display type LED indicators International Protection (IP) code Certification Operational conditions	Rackmount 1.83 m Black LCD Status IP20 CE, EAC
	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Technical details Sustainability certificates	0 - 40 °C -20 - 50 °C 0 - 95% 0 - 95%	
Ports & interfaces		Harmonized System (HS) code	85078000
USB port Serial interface Serial interface type SmartSlot	√ √ RJ-45 √	Weight & dimensions Width Depth Height	432 mm 505 mm 85 mm
Battery voltage 48 V	5 year(s)	Weight Package width Package depth Package height Package weight	21 kg 594 mm 749 mm 246 mm 29.6 kg
	✓	Packaging data Manual	√

Logistics	data
-----------	------

Products per pallet

12 pc(s)





731304340294

0731304340294

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.