DELL

DELL C7520QT interactive whiteboard 189.2 cm (74.5") 3840 x 2160 pixels Touchscreen Black

Brand : DELL
Product name : C7520QT

Product code: C7520QT

- 74.5" UHD LED IPS 3840 x 2160 Flatfrog InGlass Touch
- 8ms, 16:9, 350cd/m², 1200:1
- 1 x DP 1.2, 1 x VGA, 3 x HDMI, 6 x USB 3.0, 1 x RJ-45, 1 x RS232, 3.5 mm
74.5" (3840 x 2160) UHD IPS, Flatfrog InGlass Touch, 178°/178°, 1.07B, 1200:1, 350 cd/m², 160W

DELL C7520QT interactive whiteboard 189.2 cm (74.5") 3840 x 2160 pixels Touchscreen Black:

Write, brainstorm and increase productivity with virtually zero-lag, 20-point touch and our exclusive Dell Screen Drop feature.
DELL C7520QT. Display diagonal: 189.2 cm (74.5"), Display brightness: 350 cd/m², Display number of colours: 1.073 billion colours. Aspect ratio: 16:9. Audio output: 3.5 mm. Product colour: Black, Panel mounting interface: 400 x 400 mm, Certification: UL. Power consumption (max): 270 W, Power consumption (typical): 140 W, Power consumption (standby): 0.3 W

Features

Display diagonal *	189.2 cm (74.5")
Display brightness	350 cd/m²
Display number of colours	1.073 billion colours
Display resolution	3840 x 2160 pixels
HD type	4K Ultra HD
Panel type	IPS
Contrast ratio (typical)	1200:1
Response time	8 ms
Touchscreen *	✔
Touch technology	Multi-touch
Touchscreen type	Multi-user
Number of simultaneous touchpoints	20
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.429 x 0.429 mm
Colour gamut	72%

Audio

Built-in speaker(s) *	✔

Projector

Aspect ratio	16:9

Network

Ethernet LAN	✔

Ports & interfaces

HDMI ports quantity	3
HDMI version	2.0
DisplayPorts quantity	1
Ethernet LAN (RJ-45) ports	1
VGA (D-Sub) ports quantity	1
Audio output	3.5 mm
RS-232 ports	1

Ergonomics

Product colour	Black
VESA mounting	✔
Panel mounting interface	400 x 400 mm
Wall mountable	✔
Certification	UL

Power

Power consumption (max)	270 W
Power consumption (typical)	140 W
Power consumption (standby)	0.3 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width *	1734.8 mm
Depth	78.7 mm
Height *	1018.5 mm

Packaging content

Cables included	DisplayPort, HDMI, USB, VGA
Remote control included	✔
Quick start guide	✔
Stylus included	✔

Sustainability

Sustainability certificates	RoHS, ENERGY STAR

5397184200155

5706998990129