

## TP-Link Archer MR400 wireless router Fast Ethernet Dual-band (2.4 GHz / 5 GHz) 4G Black

Brand : TP-Link Product code: ARCHER MR400

**Product name:** Archer MR400

- Cutting-edge 4G network share internet access with up to 64 Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- AC1200 Wi-Fi creates simultaneous dual band Wi-Fi networks, with maximum speeds of up to 300 Mbps on the 2.4 GHz band and 867 Mbps on the 5 GHz band
- Plug a SIM card and play no configurations needed, compatibility for SIM cards in 100+ countries are assured by years of field tests
- Two detachable advanced LTE antennas enjoy stable and efficient connections to every device thanks to the two external antennas
- Wi-Fi router mode plug an Ethernet cable into the LAN/WAN port for flexible access as a backup option if you can't get a 4G connection
- 3x 10/100Mbps LAN, 1x 10/100Mbps LAN/WAN, SIM, 802.11ac/n/a/b/g/n, 2.4/5 GHz, 202x141x33.6 mm





WAN connection		Security	
Ethernet WAN *	✓	DoS attack prevention	1
SIM card slot *	✓	Protocols	
3G/4G USB modem compatibility *	✓	DHCP client	1
Wireless LAN features		DHCP server	✓
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)	Supported network protocols	IPv4, IPv6
Top Wi-Fi standard *	Wi-Fi 5 (802.11ac) 867 Mbit/s 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac) 450 Mbit/s	Design	
WLAN data transfer rate (max) *		Product colour	Black
Wi-Fi standards		Wall mountable	✓
WLAN data transfer rate (first band)		LED indicators	LAN, Power, Status, WLAN
WLAN data transfer rate (second	867 Mbit/s	On/off switch	✓
band)	oor marga	Product type *	Tabletop router
Network		Packaging content	
Ethernet LAN *	✓	Cables included	LAN (RJ-45)
Ethernet LAN interface type *	Fast Ethernet	AC adapter included	✓
Ethernet LAN data rates	10,100 Mbit/s	Quick installation guide	1
Cabling technology	10/100Base-T(X) IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antenna	
		Antenna design *	Internal & external
		Antennas quantity	2
Port forwarding	<b>√</b>	Detachable antenna(s)	<b>/</b>
Dynamic DNS (DDNS)	<b>√</b>	Transmit power	<20dBm(2.4GHz), <23dBm(5GHz)
VPN tunnels quantity VPN Passthrough	10  ✓ PPTP, L2TP, IPSec	Features	
VPN support		Certification	CE, RoHS
Mobile network	, 22, 350	Power	
	46	Power source type *	DC
Mobile network generation 2G standards	andards Edge, GPRS, GSM andards DC-HSPA+, HSPA, HSPA+, UMTS	Output voltage	12 V
3G standards		Output current	1.5 A
4G standard		Operational conditions	
GSM bands supported	850,900,1800,1900 MHz	Operating temperature (T-T)	0 - 40 °C
UMTS bands supported	900,2100 MHz	Storage temperature (T-T)	-40 - 70 °C

Mobile network		Operational conditions	
4G bands supported	800,900,1800,2100,2600 MHz	Operating relative humidity (H-H)	10 - 90%
Ports & interfaces		Storage relative humidity (H-H)	5 - 90%
Ethernet LAN (RJ-45) ports *	3	System requirements	
USB port *	×		Windows 10, Windows 2000,
Management features		Windows operating systems	Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Web-based management Quality of Service (QoS) support Reset button	✓ <b>X</b>	Windows operating systems supported	
WPS push button	✓	Linux operating systems supported	<b>√</b>
Security		Mac operating systems supported	✓
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Mac compatibility	1
		Weight & dimensions	
Firewall	✓	Width	174 mm
Guest access	✓	Depth	124.5 mm
Access Control List (ACL)	<b>√</b>	Height	33.5 mm
Stateful Packet Inspection (SPI)	<b>*</b>	Packaging data	
		Package width	307 mm
		Package depth	223 mm
		Package height	70 mm
		Package type	Box

