

Philips E Line 271E1SCA/00 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black

Brand : Philips

Product family: E Line

Product code: 271E1SCA/00

Product name : 271E1SCA/00

E Line 27" (68.6 cm) Full HD Curved LCD monitor

Philips E Line 271E1SCA/00 LED display 68.6 cm (27") 1920 x 1080 pixels Full HD LCD Black:

The 27" curved E-Line display offers a truly immersive experience in a stylish design. Experience crisp Full HD visuals and smooth action with AMD FreeSync technology.

Philips E Line 271E1SCA/00. Display diagonal: 68.6 cm (27"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	68.6 cm (27")	PC Audio in	✓
Display resolution *	1920 x 1080 pixels	Ergonomics	
HD type *	Full HD	VESA mounting *	✓
Native aspect ratio *	16:9	Panel mounting interface	100 x 100 mm
Display technology *	LCD	Cable lock slot *	✓
Panel type *	VA	Cable lock slot type	Kensington
Backlight type	W-LED	Height adjustment *	✗
Touchscreen *	✗	Tilt angle range	-5 - 20°
Display brightness (typical)	250 cd/m²	On Screen Display (OSD)	✓
Response time	4 ms	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Anti-glare screen	✓		
Screen shape *	Curved	Number of OSD languages	21
Screen curvature rating	1500R	Plug and Play	✓
Supported graphics resolutions	1920 x 1080 (HD 1080)	LED indicators	Operation, Stand-by
Supported video modes	1080p	Tilt adjustment	✓
Aspect ratio	16:9	Power	
Contrast ratio (typical) *	3000:1	Energy efficiency class (SDR) *	E
Maximum refresh rate *	75 Hz	Energy consumption (SDR) per 1000 hours *	21 kWh
Viewing angle, horizontal	178°	Power consumption (typical) *	33.2 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Display number of colours *	16.7 million colours	Power consumption (off)	0.3 W
Pixel pitch	0.311 x 0.311 mm	AC input voltage	100 - 240 V
Pixel density	82 ppi	AC input frequency	50 - 60 Hz
Horizontal scan range	30 - 85 kHz	Power supply type	External
Vertical scan range	48 - 76 Hz	Energy efficiency scale	A to G
Viewable size, horizontal	59.8 cm		
Viewable size, vertical	33.6 cm		
Digital horizontal frequency	30 - 85 kHz		
Digital vertical frequency	48 - 76 Hz		

Display		Operational conditions	
Display diagonal (metric)	68.6 cm	Operating temperature (T-T)	0 - 40 °C
DDC/CI	✓	Storage temperature (T-T)	-20 - 60 °C
Haze rate	25%	Operating relative humidity (H-H)	20 - 80%
Surface hardness	3H	Operating altitude	0 - 3658 m
RGB colour space	sRGB	Non-operating altitude	0 - 12192 m
Colour gamut	83%	Packaging content	
sRGB coverage (typical)	100%	Stand included	✓
NTSC coverage (typical)	83%	Cables included	HDMI, Audio (3.5mm), AC
3D	✗	Manual	✓
Separate H/V sync	✓	Weight & dimensions	
Display sRGB	✓	Width (with stand)	611 mm
Performance		Depth (with stand)	202 mm
NVIDIA G-SYNC *	✗	Height (with stand)	462 mm
AMD FreeSync *	✓	Weight (with stand)	4.5 kg
Component video sync	Separate sync, Sync-on-green (SOG)	Width (without stand)	611 mm
Flicker-free technology	✓	Depth (without stand)	43 mm
Low Blue Light technology	✓	Height (without stand)	367 mm
Multimedia		Weight (without stand)	3.81 kg
Built-in speaker(s) *	✓	Packaging data	
Built-in camera *	✗	Package width	730 mm
Number of speakers	2	Package depth	160 mm
RMS rated power	3 W	Package height	524 mm
Design		Package weight	6.7 kg
Market positioning *	Home	Package type	Box
Product colour *	Black	Sustainability	
Front bezel colour	Black	Sustainability certificates	RoHS
Feet colour	Black	European Product Registry for Energy Labelling (EPREL) code	388179
Heavy metals free	Hg (mercury)	Logistics data	
Certification	CE Mark, CU-EAC, TUV-BAUART	Harmonized System (HS) code	85285210
Ports & interfaces		Other features	
Built-in USB hub *	✗	On/off switch	✓
VGA (D-Sub) ports quantity	1	TV tuner integrated	✗
DVI port	✗	Exterior finish type	Textured
HDMI *	✓	Picture enhancement	SmartImage game
HDMI ports quantity	1	Recyclable packaging material	100%
HDMI version	1.4	Regulatory Approvals	CE Mark; CU-EAC; TUV-BAUART
Audio input	✗	LowBlue mode	✓
Headphone out *	✓	Mean time between failures (MTBF)	50000 h
Headphone outputs	1		



8712581759391

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date