



ATEN KL1116VN-AXA-EE KVM switch Rack mounting Black

Brand : ATEN

Product code: KL1116VN-AXA-EE

Product name : KL1116VN-AXA-EE



- One bus for local and one bus for remote KVM over IP access
- Virtual media enables file applications, OS patching, software installation and diagnostic testing
- High Video Resolutions - up to 1920 x 1200 @ 60 Hz with 24-bit color depth at the switch's external local console and on remote displays; up to 1280 x 1024 @ 75 Hz at the switch's built-in LCD screen
- Exclusive LED illumination light designed by ATEN to illuminate the keyboard and touchpad to allow visibility in lowlight conditions

16-Port Cat 5 Dual Rail LCD KVM over IP Switch 1 local / 1 remote user access

ATEN KL1116VN-AXA-EE. Keyboard port type: USB, Mouse port type: USB, Video port type: DVI-D/VGA.

Cabling technology: 10/100/1000Base-T(X). HD type: WUXGA, Maximum resolution: 1920 x 1200 pixels, Video bandwidth: 60 Hz. Product colour: Black, Rack capacity: 1U, Housing material: Metal. Display: LCD, Display diagonal: 48.3 cm (19")



Ports & interfaces		Display	
Number of computers controlled *	16	Built-in display *	✓
Keyboard port type *	USB	Display	LCD
Mouse port type *	USB	Display diagonal	48.3 cm (19")
Video port type *	DVI-D/VGA	On Screen Display (OSD)	✓
DVI-D ports quantity	1	Power	
VGA (D-Sub) ports quantity	1	Power source	AC
Console ports *	DVI-D, USB A, VGA (D-Sub)	AC input voltage	100 - 240 V
Console USB ports quantity	2	AC input frequency	50 - 60 Hz
USB connector type	USB Type-A	Input current	1 A
Network		System requirements	
Ethernet LAN	✓	Windows operating systems supported	✓
Ethernet LAN (RJ-45) ports	2	Linux operating systems supported	✓
Cabling technology	10/100/1000Base-T(X)	Mac operating systems supported	✓
Performance		Operational conditions	
HD type *	WUXGA	Operating temperature (T-T)	0 - 40 °C
Maximum resolution *	1920 x 1200 pixels	Storage temperature (T-T)	-20 - 60 °C
Video bandwidth	60 Hz	Operating relative humidity (H-H)	0 - 80%
Scan interval	1,255 s	Weight & dimensions	
DDC2B support	✓	Width	701.2 mm
Firmware upgradeable	✓	Depth	480 mm
Design		Height	44 mm
Rack mounting *	✓	Weight	15.3 kg
Rack capacity	1U	Packaging content	
Product colour *	Black	Rack mount kit	✓
Housing material	Metal		
Cascadable	✓		
LED indicators	✓		
Push button	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-MAR-2024. Prints or copies of Information are only valid on the printed Publication date