


Epson TM-H6000V-216B1 180 x 180 DPI Wired Thermal POS printer

Brand : Epson **Product code:** C31CG62216B1

Product name: TM-H6000V-216B1







Printing		Features	
Maximum resolution Print columns Print speed Print speed	180 x 180 DPI 40 dots/line 5.7 lps 350 mm/sec	Certification	CE, EN55024, EN55032 A, IEC61000-4-2, IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-11, 2014/30 / US
Character sets	ANK	Design	
Print technology * Type *	Thermal POS printer	Product colour *	Black
Paper handling	r oo printer	Power	
Maximum roll diameter	8.3 cm	Power source type *	USB
Ports & interfaces		DC output voltage	24 V
USB port *	1	Operational conditions	
USB 2.0 ports quantity USB connector Connectivity technology * Ethernet LAN (RJ-45) ports	2 USB Type-A / USB Type-B Wired 1	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	5 - 45 °C -10 - 50 °C 10 - 90% 10 - 90%
Standard interfaces	Ethernet, USB 1.1, USB 2.0	System requirements	
Network		Pre-installed software	Server Direct Print, ePOS Display, ePOS-Print
Ethernet LAN * Ethernet LAN data rates	√ 10,100 Mbit/s	Weight & dimensions	
Wi-Fi *	10,100 MBR/S	Width	186 mm
Features		Depth	278 mm
Sound pressure level (printing)	55 dB	Height Weight	181 mm 4.4 kg
Cutter	✓	Packaging data	4.4 Kg
Autocutter durability	3 million cuts	Quantity per pack	1 nc/s)
Print head life	200 km	Package width	1 pc(s) 295 mm
Country of origin Ribbon life	China 4000000 million characters	Package depth	382 mm
NIDDON IIIE	Middle of Paper pass sensor, Front	Package height	293 mm
	cover open sensor (détecteur de couvercle avant ouvert), Roll paper cover open sensor, Paper End Sensor (détecteur de fin de rouleau), Top of Form sensor, Bottom of Form sensor (détecteur de bas de formulaire), Slip eject sensor, Receipt near-end sensor	Package weight	5.5 kg
		Packaging content	
Built-in sensors details		Quick start guide	✓
		Logistics data	
		Harmonized System (HS) code	84433210
		Other features	
		Buffer size Print head life	4 KB 200000000 million characters



8715946676111

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.