Manhattan DisplayPort 1.1 to HDMI Cable, 1080p@60Hz, 1.8m, Male to Male, DP With Latch, Black, Not Bi-Directional, Three Year Warranty, Polybag

Brand : Manhattan

Product code: 152679

Product name : DisplayPort 1.1 to HDMI Cable, 1080p@60Hz, 1.8m, Male to Male, DP With Latch, Black, Not Bi-Directional, Three Year Warranty, Polybag

DisplayPort to HDMI Cable, 1080p, 1.8m, Male to Male, 1080p@60Hz (1920x1080p), Black

Straight

Manhattan DisplayPort 1.1 to HDMI Cable, 1080p@60Hz, 1.8m, Male to Male, DP With Latch, Black, Not Bi-Directional, Three Year Warranty, Polybag:

An indispensable companion for your DisplayPort PC

For the simplest and most discreet installation, this DisplayPort to HDMI cable connects your DisplayPort video source to the HDMI port on your display. It doesn't need a power source, unlike some converter dongles that require active power and separate bulky video cabling. This cable lets you enjoy movies on a big-screen HDTV, extend your desktop to a second monitor (up to 1080p) for an expanded workspace, or show presentations on a projector at school or work without needing any other adapter or converter. Manhattan DisplayPort 1.1 to HDMI Cable, 1080p@60Hz, 1.8m, Male to Male, DP With Latch, Black, Not Bi-Directional, Three Year Warranty, Polybag. Cable length: 1.8 m, Connector 1: DisplayPort, Connector 2: HDMI. Sustainability certificates: RoHS. Weight: 110 g. Quantity per pack: 1 pc(s)







Features

supported

Connector 1 form factor
Connector 2 form factor
Connector contacts plating
Cable length *
Connector 1 *
Connector 2 *
Connector 1 gender *
Connector 2 gender *
HDCP
DisplayPort version
Maximum resolution
Supported video modes
Maximum refresh rate
Product colour
Jacket material
Plug material
Plug and Play
Windows operating systems

Straight Gold 1.8 m DisplayPort HDMI Male Male 1 1.1 1920 x 1080 pixels 1080p 60 Hz Black Polyvinyl chloride (PVC) Acrylonitrile butadiene styrene (ABS) 1

Features		
Mac operating systems supported Connector gender Linux operating systems supported Certification	✓ Male/Male ✓ CE, FCC	
Operational conditions		
Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C -20 - 60 °C 0 - 96%	
Sustainability		
Sustainability certificates	RoHS	
Weight & dimensions		
Weight	110 g	
Packaging data		
Quantity per pack	1 pc(s)	
Technical details		
Harmonized System (HS) code	84733080	





766623152679

0766623152679

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.