

Toshiba BA410T label printer Thermal transfer 300 x 300 DPI Wired & Wireless

Brand : Toshiba

Product code: BA410T-TS12-QM-S

Product name : BA410T



- Extensible OS architecture fit for future trends
 - Improved productivity thanks to increased print speed with superior print quality
 - Outstanding reliability and robustness to eliminate almost any downtime
 - Easy to use high performance printer suitable for versatile environments
 - Wide range of features and options to adapt to ever-changing workplaces
 - SOTI Connect certified for IoT device management
- 300 dpi, 11.8 dots/mm, Thermal transfer, LCD, 128 MB FROM / 128 MB SRAM, AC 100-240 V, 50/60 Hz, 245 x 414 x 333 mm, 15 kg

Toshiba BA410T label printer Thermal transfer 300 x 300 DPI Wired & Wireless:

Built on the renowned mechanical platform of its predecessor, the Toshiba BA410T retains all the superb reliability and robustness – even in rugged environments.

The Toshiba BA410T with its entirely new software platform ensures it will keep pace even with the latest technology standards and requirements. Thanks to future-proof options and a broad set of features, the BA410T offers solutions that are usually reserved for industrial printers only.

Printing		Design	
Print technology *	Thermal transfer	Product colour *	Black
Colour *	✗	Display *	LCD
Maximum resolution *	300 x 300 DPI	Display resolution	128 x 64 pixels
Printable dot numbers	11.8 dot	Colour display	✗
Print speed *	203.2 mm/sec	Control type	Buttons
Printing colours	Black	Power	
Maximum printing width *	10.6 cm	AC input voltage	100 - 240 V
Minimum print length	1.1 cm	AC input frequency	50/60 Hz
Text alignment	Center	System requirements	
Printing characters	2D barcode, Barcode	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1
Maximum print length	1.498 m	Server operating systems supported	Windows Server 2008 R2, Windows Server 2012, Windows Server 2016
Paper handling		Mobile operating systems supported	Android, Windows Mobile, iOS
Ribbon width	11 cm	Linux operating systems supported	✓
Ribbon length	450 m	Operational conditions	
Maximum roll diameter	20 cm	Operating relative humidity (H-H)	25 - 85%
Media thickness	0.1 - 0.17 mm	Storage relative humidity (H-H)	10 - 90%
Supported paper width	22 - 114 mm	Operating temperature (T-T)	5 - 40 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 60 °C
Connectivity technology *	Wired & Wireless	Weight & dimensions	
Ethernet LAN *	✓	Width	245 mm
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Depth	414 mm
Bluetooth	✓	Height	333 mm
Bluetooth version	2.1+EDR	Weight	15 kg
USB port *	✓	Other features	
Parallel ports quantity	1	Media types supported	Vellum paper and labels, matt coated paper, glossy coated paper, synthetic film, PET film, polyimide
RS-232 ports	1	Keys quantity	3 keys
Performance			
Page description languages	ZPL II		
Internal memory	128 MB		
Flash memory	128 MB		

Performance

Built-in barcodes

AZTECCODE, Code 39, Code 93,
Code-128 Codabar Library, Code-39
Library, Data Matrix, EAN128, GS1
DataBar, GS1 DataMatrix, Industrial
2/5, Interleaved 2/5, MSI, Matrix 2/5,
MaxiCode, Micro QR Code,
MicroPDF417, PDF417, POSTNET,
QR Code, UPC-A, UPC-E

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.