Sony SRG-X400 Dome IP security camera 3840 x 2160 pixels Ceiling/Pole

Brand : Sony Product code: SRG-X400BC

Product name: SRG-X400

IP, 1/2.5 Exmor R CMOS, 8.5MP, f = 4.4 - 88mm, PTZ, HDMI, RS-422, RJ45, Black Sony SRG-X400. Type: IP security camera, Connectivity technology: Wired, PTZ modes: Digital PTZ. Mounting type: Ceiling/Pole, Product colour: Black, Form factor: Dome. Minimum illumination: 1.6 Ix, Lens viewing angle, horizontal: 70° , Tilt angle range: $-20 - 90^\circ$. Sensor type: Exmor, Optical sensor size: 25.4 / 2.5mm (1 / 2.5"). Digital zoom: 40x, Focus: Motorized/Manual, Focal length range: 4.4 - 88 mm





Performance		Video	
Type * Connectivity technology * PTZ control PTZ modes Preset points Wide Dynamic Range (WDR) Day/night mode Remote viewing Infrared (IR) cut-off filter	IP security camera Wired Digital PTZ	Video intelligence analytic Video streaming Noise reduction Gain control type Flip & mirror Image stabilizer Bit rate control Bit rate	Auto/Manual Auto/Manual Constant Bit Rate (CBR)/Variable Bit Rate (VBR) State (VBR)
Plug and Play	✓	Audio	
Design Form factor * Mounting type *	Dome Ceiling/Pole	Audio output channels Audio codecs Voice codecs	2 channels AAC LC 128 kbps, AAC LC 256 kbps AAC
Product colour *	Black	Network	
LED indicators Camera	LAN, Power	Ethernet LAN *	IPv4, IPv6, TCP, UDP, ARP, ICMP,
Camera pan control Camera tilt control	1	Supported network protocols	IGMP, HTTP, HTTPS, DHCP, DNS, RTP/RTCP, RTSP, UPnP, VISCA over IP
Minimum illumination	1.6 lx	Streaming method	Multicast
Lens viewing angle, horizontal	70°	Ports & interfaces	
Tilt angle range -20 - 90° Tilt speed 120 °/sec Pan range -170 - 170° Pan speed 300 °/sec Auto flip White balance -20 - 90° Auto, Indoor, Manual, One push, Outdoor	Ethernet LAN (RJ-45) ports RS-422 ports Microphone in HDMI ports quantity Terminal block port DC-in jack	1 1 ✓ 1	
Camera shutter speed	1/1 - 1/10000 s	Security	
Image sensor Number of sensors Optical sensor size	1 25.4 / 2.5 mm (1 / 2.5")	Anti-flicker Mirror Digital watermark	✓ ✓
Sensor type *	Exmor	Management features	
Lens system Zoom capability Digital zoom	√ 40x	Web-based management Firmware upgradeable Remotely operated	√ √
Focus	Motorized/Manual	Power	
Maximum aperture number Minimum aperture number Focal length range	3.8 2 4.4 - 88 mm	Power source type * Power consumption DC output voltage	DC, PoE 25.5 mA 12

Lens system		Operational conditions	
Closest focusing distance	0.08 m	Operating temperature (T-T)	0 - 40 °C
Night vision		Storage temperature (T-T)	-20 - 60 °C
Night vision *	✓	Weight & dimensions	
LED type	IR	Width	158.4 mm
Video		Depth	200.2 mm
Maximum resolution * Total megapixels *	3840 x 2160 pixels 8.5 MP	Height Weight	177.5 mm 1.8 kg
. otal megapines	0.5		
Video compression formats	H.264, H.265	Packaging content	
5 ,	H.264, H.265 640 x 360, 720 x 480, 720 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160 720p, 1080i, 1080p, 2160p	Number of cameras * Mounting kit Mounting brackets included Screws included	1 ✓ ✓
Video compression formats Supported graphics resolutions Supported video modes	H.264, H.265 640 x 360, 720 x 480, 720 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160	Number of cameras * Mounting kit Mounting brackets included	1 ✓ ✓
Video compression formats Supported graphics resolutions Supported video modes	H.264, H.265 640 x 360, 720 x 480, 720 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 3840 x 2160 720p, 1080i, 1080p, 2160p	Number of cameras * Mounting kit Mounting brackets included Screws included	1 */ */ */ */



4548736104785

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.