

Lindy 140m 4 Port USB 2.0 Cat.6 Extender

Brand : Lindy Product code: 42710

Product name: 140m 4 Port USB 2.0 Cat.6 Extender

- Extends the distance of 4 USB 2.0 peripherals by up to 140m
- Connect devices using standard Cat.6 UTP or higher network cables (not included)
- Supports USB 2.0 High-Speed transfer rates up to 480Mbps
- Robust aluminium housing with mounting points
- 2-year warranty

140m 4 Port USB 2.0 Cat.6 Extender

Lindy 140m 4 Port USB 2.0 Cat.6 Extender. Type: Transmitter & receiver, Connectivity technology: Wired, Maximum transfer distance: 140 m. AC adapter output voltage: 5 V, AC adapter output current: 2.6 A. Transmitter width: 12 cm, Transmitter depth: 6.7 cm, Transmitter height: 2.7 cm. Package width: 240 mm, Package depth: 150 mm, Package height: 55 mm. Cables included: USB Type-A to USB Type-B, Included power plug types: EU, UK, US





| Features | | Operational conditions | |
|---|--|---|--|
| Connectivity technology * Wire | Transmitter & receiver Wired | Operating relative humidity (H-H) | 0 - 95% |
| | | Weight & dimensions | |
| Maximum transfer distance Cable types supported Product colour Material USB 2.0 ports quantity USB data transfer rates LED indicators Certification | 140 m Cat5e, Cat6 Black Aluminium 5 480 Mbit/s ✓ CE, FCC, RoHS & REACH, CP65 | Transmitter width Transmitter depth Transmitter height Transmitter weight Receiver width Receiver depth Receiver height Receiver weight | 12 cm 6.7 cm 2.7 cm 190 g 13 cm 6.7 cm 2.7 cm 210 g |
| Transmitter | | Packaging data | · J |
| RJ-45 ports quantity (transmitter) | 1 | Package width | 240 mm |
| Receiver | | Package depth | 150 mm |
| RJ-45 ports quantity (receiver) | 1 | Package height | 55 mm |
| Power | | Package weight | 1.32 kg |
| AC adapter output voltage | 5 V | Packaging content | |
| AC adapter output current | 2.6 A | AC adapter included | ✓ |
| Operational conditions | | Cables included | USB Type-A to USB Type-B |
| Operating temperature (T-T) Storage temperature (T-T) | 0 - 55 °C -20 - 85 °C | Manual Included power plug types | ₹ EU, UK, US |
| | | Logistics data | |
| | | Harmonized System (HS) code | 84733080 |



4002888427104

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.