## ASUS ZenWiFi AX (XT8) wireless router Gigabit Ethernet Tri-band (2.4 GHz / 5 GHz / 5 GHz) 4G White

**Brand**: ASUS **Product code**: 90IG0590-M03G30

Product name: ZenWiFi AX (XT8)

ZenWiFi AX (XT8), 802.11a/b/g/n/ac/ax, 2.4 + 5 GHz, 512 MB RAM, RJ-45, USB 3.1, MU-MIMO, 160x75x161.5 mm, white

ASUS ZenWiFi AX (XT8). WAN connection type: RJ-45. Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN data transfer rate (max): 6600 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 1000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Mobile network generation: 4G. Security algorithms: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPS, NAT functionality: PPTP, L2TP, IPSec, RTSP, H.323, SIP, PPPOE



WAN connection		Security	
Ethernet WAN * DSL WAN * SIM card slot * WAN connection type	<b>X X R</b> J-45	Filtering URL filtering System event log DMZ support Network address translation (NAT)	<b>V V V V V</b>
Wireless LAN features Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)	NAT functionality	PPTP, L2TP, IPSec, RTSP, H.323, SIP,
Top Wi-Fi standard * WLAN data transfer rate (max) *	Wi-Fi 6 (802.11ax) 6600 Mbit/s	Protocols	PPPoE
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Universal Plug and Play (UPnP)  Design	<b>7</b>
Modulation	1024-QAM	Product colour On/off switch	White
Network		Product type *	Tabletop router
Ethernet LAN * Ethernet LAN interface type *	✓ Gigabit Ethernet	Antenna	
Ethernet LAN data rates	1000 Mbit/s IEEE 802.11a, IEEE 802.11ac, IEEE	Antenna design * Antennas quantity	Internal 6
Networking standards	802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Features	
Port forwarding Dynamic DNS (DDNS) VPN Passthrough VPN support	✓ ✓ IPSec, PPTP, L2TP, PPTP, OpenVPN	Built-in processor Processor frequency Processor cores Internal memory	1500 MHz 4 512 MB
Mobile network		Flash memory	256 MB
Mobile network generation 3G 4G	4G <b>X</b> <b>X</b>	Power Power source type * AC input voltage	AC 110 - 240 V
Ports & interfaces		AC input frequency Output voltage	50/60 Hz 19 V
Ethernet LAN (RJ-45) ports *	3	Output current	1.75 A
USB port * USB 3.2 Gen 1 (3.1 Gen 1) Type-A	1	System requirements	
ports quantity Memory card slot(s)	×	Windows operating systems supported	Windows 10, Windows 7, Windows 8
Management features		Mac operating systems supported	Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion
Web-based management Quality of Service (QoS) support	<b>√</b>	Weight & dimensions	
Reset button WPS push button	<b>✓</b>	Width Depth Height Weight	160 mm 75 mm 161.5 mm 716 g

Security		Packaging data	
	WPA-Enterprise, WPA-PSK, WPA2-	Number of products included	1 pc(s)
Firewall	Enterprise, WPA2-PSK, WPS	Logistics data	
Guest access		Harmonized System (HS) code	85176990
Stateful Packet Inspection (SPI)	✓		
DoS attack prevention	✓		

