ASUS ZenWiFi AX (XT8) wireless router Gigabit Ethernet Tri-band (2.4 GHz / 5 GHz / 5 GHz) 4G White

Brand: ASUS **Product code**: 90IG0590-M03G40

Product name: ZenWiFi AX (XT8)

ZenWiFi AX (XT8), 802.11a/b/g/n/ac/ax, 2.4 + 5 GHz, 512 MB RAM, RJ-45, USB 3.1, MU-MIMO, 160x75x161.5 mm, white, 2 pcs

ASUS ZenWiFi AX (XT8). WAN connection type: RJ-45. Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN data transfer rate (max): 6600 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 1000 Mbit/s, Networking standards: IEEE 802.11a, IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n. Mobile network generation: 4G. Security algorithms: WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPS, NAT functionality: PPTP, L2TP, IPSec, RTSP, H.323, SIP, PPPOE





WAN connection		Security	
Ethernet WAN * DSL WAN * SIM card slot * WAN connection type	✓ × × RJ-45	Filtering URL filtering System event log DMZ support	* * * * *
Wireless LAN features		Network address translation (NAT)	✓
Wi-Fi band * Top Wi-Fi standard *	Tri-band (2.4 GHz / 5 GHz / 5 GHz) Wi-Fi 6 (802.11ax)	NAT functionality	PPTP, L2TP, IPSec, RTSP, H.323, SIP, PPPoE
WLAN data transfer rate (max) *	6600 Mbit/s	Protocols	
	802.11a, 802.11b, 802.11g, Wi-Fi 4	Universal Plug and Play (UPnP)	✓
Wi-Fi standards	(802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax)	Design	
Modulation	1024-QAM	Product colour	White
Network		On/off switch	Tableton variton
Ethernet LAN *	√	Product type *	Tabletop router
Ethernet LAN interface type *	Gigabit Ethernet	Antenna	
Ethernet LAN data rates	1000 Mbit/s IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11q, IEEE 802.11n	Antenna design * Antennas quantity	Internal 6
Networking standards		Features	
Port forwarding Dynamic DNS (DDNS) VPN support	✓ ✓ IPSec, PPTP, L2TP, PPTP, OpenVPN	Built-in processor Processor frequency Processor cores	1500 MHz 4
Mobile network		Internal memory Flash memory	512 MB 256 MB
Mobile network generation	4G	Power	230 1410
3G 4G	×	Power source type * AC input voltage	AC 110 - 240 V
Ports & interfaces		AC input frequency	50/60 Hz
Ethernet LAN (RJ-45) ports *	3	Output voltage	19 V
USB port *	1	Output current	1.75 A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	System requirements	
Memory card slot(s)	×	Windows operating systems	Windows 10, Windows 7, Windows 8
Management features		supported	Mac OS X 10.6 Snow Leopard, Mac
Web-based management Quality of Service (QoS) support Reset button	√ √ √	Mac operating systems supported	OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion

Management features		Weight & dimensions	
WPS push button	√	Width	160 mm
Security		Depth	75 mm
Security algorithms	WPA-Enterprise, WPA-PSK, WPA2- Enterprise, WPA2-PSK, WPS ✓	Height	161.5 mm
		Weight	716 g
Firewall		Packaging data	
Guest access		Number of products included	2 pc(s)
Stateful Packet Inspection (SPI)	✓	Logistics data	
DoS attack prevention	1		
		Harmonized System (HS) code	85176990

