Intellinet 16-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports, LCD Display, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 370 W, Endspan, 19" Rackmount (UK 3-pin plug)

Brand : Intellinet

Product name : 16-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports, LCD Display, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 370 W, Endspan, 19" Rackmount (UK 3-pin plug)

Product code: 561259-UK

16-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports, LCD Display, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 370 W, Endspan, 19" Rackmount (UK 3-pin plug)
Intellinet 16-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports, LCD Display, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 370 W, Endspan, 19" Rackmount (UK 3-pin plug). Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Full duplex. MAC address table: 8192 entries, Switching capacity: 36 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE). Rack mounting

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	16
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)
SFP module slots quantity	2

Network

Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Copper ethernet cabling technology	100BASE-TX, 1000BASE-T
Full duplex	✔
Flow control support	✔
Auto MDI/MDI-X	✔

Data transmission

Switching capacity *	36 Gbit/s
MAC address table *	8192 entries
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps

Design

Rack mounting *	✔
Product colour	Black
Housing material	Metal
LED indicators	Activity, Link, PoE, Power
Number of fans	2 fan(s)
Certification	FCC Class A, CE, RoHS

Performance

Noise level	21.3 dB
Mean time between failures (MTBF)	144000 h

Power

AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power consumption (max)	420 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✔
Power over Ethernet (PoE) type supported	PoE+
Power over Ethernet (PoE) power per port	30 W
Total Power over Ethernet (PoE) budget	370 W

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-10 - 75 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	441.1 mm
Depth	204.3 mm
Height	44 mm
Weight	4 kg

Packaging data

Cables included	AC
Manual	✔
Package type	Box
Rack mount kit	✔

0766623995757

766623995757