

Intellinet 8-Port Fast Ethernet PoE+ Switch, 4 x PoE IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE) ports, 4 x Standard RJ45 Ports, Endspan, Desktop, 19" Rackmount (UK 3-pin plug)



Brand : Intellinet

Product code: 561075-UK

Product name : 8-Port Fast Ethernet PoE+ Switch, 4 x PoE IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE) ports, 4 x Standard RJ45 Ports, Endspan, Desktop, 19" Rackmount (UK 3-pin plug)

8-Port Fast Ethernet PoE+ Switch, 4 x PoE IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE) ports, 4 x Standard RJ45 Ports, Endspan, Desktop, 19" Rackmount (UK 3-pin plug)

Intellinet 8-Port Fast Ethernet PoE+ Switch, 4 x PoE IEEE 802.3at/af Power-over-Ethernet (PoE+/PoE) ports, 4 x Standard RJ45 Ports, Endspan, Desktop, 19" Rackmount (UK 3-pin plug). Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 2000 entries, Switching capacity: 1.6 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting

Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *	8	AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	AC input frequency	50/60 Hz
Power connector	AC-in jack	Power consumption (max)	80 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) *	✓
Copper ethernet cabling technology	10BASE-T, 100BASE-TX	Power over Ethernet (PoE) type supported	PoE+
Full duplex	✓	Power over Ethernet (PoE) power per port	30 W
Flow control support	✓	Total Power over Ethernet (PoE) budget	70 W
Auto MDI/MDI-X	✓	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 40 °C
Switching capacity *	1.6 Gbit/s	Storage temperature (T-T)	-10 - 70 °C
MAC address table *	2000 entries	Operating relative humidity (H-H)	10 - 90%
Store-and-forward	✓	Weight & dimensions	
Packet forwarding rate (100 Mbps)	148800 pps	Width	280 mm
Packet forwarding rate (10 Mbps)	14880 pps	Depth	179 mm
Design		Height	44 mm
Rack mounting *	✓	Weight	1.5 kg
Product colour	Black	Packaging data	
Housing material	Metal	Cables included	AC
LED indicators	Activity, Link, PoE, Power	Manual	✓
Certification	FCC Class A, CE	Rack mount kit	✓



0766623995672



766623995672

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.