



Manhattan Mini DisplayPort 1.2 Cable (Clearance Pricing), 4K@60Hz, 1m, Male to Male, Bi-Directional, White, Equivalent to Startech MDPMM1MW, Lifetime Warranty, Polybag

Brand : Manhattan

Product code: 324557

Product name : Mini DisplayPort 1.2 Cable (Clearance Pricing), 4K@60Hz, 1m, Male to Male, Bi-Directional, White, Equivalent to Startech MDPMM1MW, Lifetime Warranty, Polybag



Mini DisplayPort to DisplayPort Cable, 4Kx2K@60Hz, 1m, 14.8Gbps, Bi-Directional, Fully Shielded, White, Polybag

[Manhattan Mini DisplayPort 1.2 Cable \(Clearance Pricing\), 4K@60Hz, 1m, Male to Male, Bi-Directional, White, Equivalent to Startech MDPMM1MW, Lifetime Warranty, Polybag:](#)

High-definition performance for personal computing.

Manhattan Mini DisplayPort cables deliver both high-definition digital audio and video signals between desktop or notebook computers and an output device. The 20-pin connector is small and compact but offers 14.8 Gbps bandwidth, Deep colour and 24-bit, 8-channel uncompressed audio capability. It's ideal for use with DisplayPort-equipped computers, flat-panel displays, slim-profile devices and many consumer electronics including Blu-ray players and game consoles. Full foil and braided shielding, moulded boots with strain relief, protective PVC jackets and gold-plated connections ensure that Manhattan DisplayPort Cables provide maximum conductivity and clear, crisp signal transmissions with reduced EMI interference and distortion.

Features		Features	
Connector 1 form factor	Straight	Jacket material	Acrylonitrile butadiene styrene (ABS)
Connector 2 form factor	Straight	AWG wire size	32
Connector contacts plating	Gold	Data transfer rate	14.8 Gbit/s
DisplayPort version	1.2	Certification	UL 20276 ISO 9002
Maximum resolution *	4096 x 2160 pixels	Operational conditions	
Maximum refresh rate	60 Hz	Operating temperature (T-T)	0 - 50 °C
Cable length *	1 m	Storage temperature (T-T)	-25 - 85 °C
Connector 1 *	Mini DisplayPort	Operating relative humidity (H-H)	0 - 96%
Connector 2 *	Mini DisplayPort	Packaging data	
Connector 1 gender *	Male	Weight	44 g
Connector 2 gender *	Male	Quantity per pack	1 pc(s)
Product colour *	White	Package type	Polybag
Magnetically shielded	✓	Logistics data	
Cable shielding	Aluminum mylar foil	Harmonized System (HS) code	84733080



0766623324557



766623324557

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-NOV-2023. Prints or copies of Information are only valid on the printed Publication date