Viewsonic IFP2410 interactive whiteboard 59.9 cm (23.6") 1920 x 1080 pixels Touchscreen Black

Brand : Viewsonic

Product code: IFP2410-BKA-EU0

Product name : IFP2410

- Interactive front-facing teaching and collaboration
- myViewBoard® digital whiteboard software
- ViewBoard® Cast Content Sharing Software
- Android 8.1 embedded OS
- HDMI output to external display

24" FHD (1920x1080) IPS, Rockchip RK3288W Cortex-A17 Quad-Core 1.8GHz, 2GB DDR3, HDMI, 3.5mm, CardReader, 4 x USB 2.0, USB type-B, 5.6kg, Android 8.1 Oreo

Viewsonic IFP2410. Display diagonal: 59.9 cm (23.6"), Working area: 545 x 321 mm, Display brightness: 250 cd/m². Maximum internal memory: 16 GB, RAM capacity: 2 GB, RAM type: DDR3. Speaker power: 5 W. USB connector type: USB Type-A. Product colour: Black, Panel mounting interface: 100 x 100 mm

Features	
Display diagonal *	59.9 cm (23.6")
Display brightness	250 cd/m²
Display number of colours	16.78 million colours
Display resolution	1920 x 1080 pixels
HD type	Full HD
Panel type	IPS
Contrast ratio (typical)	3000:1
Response time	15 ms
Touchscreen *	✓
Touch technology	Multi-touch
Touchscreen type	Capacitive
Number of simultaneous touchpoints	10
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Working area *	545 x 321 mm

Computer system	
Built-in processor	✓
Maximum internal memory	16 GB
RAM capacity	2 GB
RAM type	DDR3

Audio	
Built-in speaker(s) *	✓
Number of built-in speakers	2
Speaker power	5 W

Projector	
Built-in projector *	✗

Network	
Ethernet LAN	✓

Ports & interfaces	
USB 2.0 ports quantity	4
USB connector type	USB Type-A
USB 2.0 Type-B Touch ports quantity	1

Ports & interfaces	
HDMI ports quantity	2
HDMI output ports quantity	1
Ethernet LAN (RJ-45) ports	1
Line-in	✓

Ergonomics	
Product colour	Black
VESA mounting	✓
Panel mounting interface	100 x 100 mm

Performance	
Card reader integrated	✓
Compatible memory cards	SD, SDHC

Power	
Power consumption (max)	40 W
Power consumption (typical)	35 W
Power consumption (off)	0.5 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz

Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Operating relative humidity (H-H)	20 - 90%

Weight & dimensions	
Width *	572.9 mm
Depth	47 mm
Height *	351.8 mm
Weight	5.64 kg

Packaging data	
Package width	643 mm
Package depth	435 mm
Package height	140 mm
Package weight	7.56 kg
Quantity per pack	1 pc(s)

Packaging content	
Cables included	AC
Quick start guide	✓

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2023. Prints or copies of Information are only valid on the printed Publication date