## ₽TlA

## T1A DELL Latitude E5250 Refurbished Laptop 31.8 cm (12.5") HD Intel® Core™ i5 i5-5200U 8 GB DDR3L-SDRAM 128 GB SSD Windows 10 Pro Black

Brand: T1A Product code: L-E5250-UK-P001

Product name: DELL Latitude E5250 Refurbished

- Windows 10 Pro 64-bit
- Intel Core i5-5200U (3MB Cache, 2.2GHz)
- 31.8 cm (12.5") HD 1366 x 768
- 8GB DDR3L-SDRAM & 128GB SSD

Intel Core i5-5200U (3MB Cache, 2.2GHz), 8GB DDR3L-SDRAM, 128GB SSD, 31.8 cm (12.5") HD 1366 x 768, Intel HD Graphics 5500, LAN, Webcam, Windows 10 Pro 64-bit

T1A DELL Latitude E5250 Refurbished. Product type: Laptop, Form factor: Clamshell. Processor family: Intel® Core™ i5, Processor model: i5-5200U, Processor frequency: 2.2 GHz. Display diagonal: 31.8 cm (12.5"), HD type: HD, Display resolution: 1366 x 768 pixels. Internal memory: 8 GB, Internal memory type: DDR3L-SDRAM. Total storage capacity: 128 GB, Storage media: SSD. On-board graphics card model: Intel® HD Graphics 5500. Operating system installed: Windows 10 Pro. Product colour: Black











Design		Keyboard	
Product type * Product colour * Form factor * Refurbished	Laptop Black Clamshell ✓	Pointing device Keyboard language Numeric keypad * Keyboard backlit	Touchpad UK English
Display		Software	
Display diagonal * Display resolution *	31.8 cm (12.5") 1366 x 768 pixels	Operating system architecture Operating system installed *	64-bit Windows 10 Pro
Touchscreen *		Processor special features	
HD type LED backlight	HD <b>√</b>	Intel® Wireless Display (Intel® WiDi)	✓
Native aspect ratio	16:9	Intel® Smart Response Technology	✓
Processor		Intel® Identity Protection Technology (Intel® IPT)	✓
Processor manufacturer * Processor generation	Intel 5th gen Intel® Core™ i5	Intel® Hyper Threading Technology (Intel® HT Technology)	<b>√</b>
Processor family *	Intel® Core™ i5	Intel® Turbo Boost Technology	2.0
Processor model * Processor frequency *	i5-5200U 2.2 GHz	Intel® Small Business Advantage (Intel® SBA)	✓
Processor boost frequency Processor threads	2.7 GHz 4	Enhanced Intel SpeedStep Technology	✓
System bus rate Processor cores	5 GT/s 2	Intel® Clear Video HD Technology (Intel® CVT HD)	✓
Processor cache	2 3 MB	Intel Clear Video Technology	✓
Processor cache type	Smart Cache	Intel® InTru™ 3D Technology	✓
Processor socket	BGA 1168	Intel® Insider™	✓
Processor lithography	14 nm	Intel® Quick Sync Video Technology	1
Processor operating modes	32-bit, 64-bit	Intel Flex Memory Access	✓
Processor series	Intel® Core™ i5-5200 Mobile Series	Intel® AES New Instructions (Intel® AES-NI)	✓
Processor codename	Broadwell	Intel Enhanced Halt State	✓

D		B	
Processor		Processor special features	
Bus type	DMI2	Intel VT-x with Extended Page Tables (EPT)	✓
Stepping The grand Decision Beauty (TDD)	F0	Intel® Secure Key	<b>✓</b>
Thermal Design Power (TDP)	15 W	Intel® OS Guard	,
Configurable TDP-down	7.5 W	Intel® Clear Video Technology for	•
Configurable TDP-down frequency Tjunction	0.6 GHz 105 °C	Mobile Internet Devices (Intel CVT	✓
Maximum number of PCI Express		for MID)	
lanes	12	Intel 64	<b>√</b>
PCI Express slots version	2.0	Execute Disable Bit	<b>V</b>
PCI Express configurations	4x1, 2x4	Idle States	<b>V</b>
Memory		Thermal Monitoring Technologies	40 y 24 y 1 2 mam
•	9 CP	Processor package size	40 x 24 x 1.3 mm
Internal memory * Internal memory type	8 GB DDR3L-SDRAM	Supported instruction sets Processor code	AVX 2.0, SSE4.1, SSE4.2 SR23Y
Memory form factor	SO-DIMM	CPU configuration (max)	1
Memory slots	2x SO-DIMM	Embedded options available	X
Maximum internal memory *	16 GB	Graphics & IMC lithography	14 nm
		Intel Virtualization Technology for	
Storage		Directed I/O (VT-d)	✓
Total storage capacity *	128 GB	Intel Identity Protection Technology	1.00
Storage media *	SSD	version	=:=#
Total SSDs capacity	128 GB	Intel Smart Response Technology version	1.00
Number of SSDs installed	1	Intel Secure Key Technology version	1.00
SSD capacity	128 GB	Intel Small Business Advantage	
Optical drive type *	X	(SBA) version	1.00
Card reader integrated	<b>√</b>	Intel Virtualization Technology (VT-	<b>√</b>
Compatible memory cards	SD	x)	*
Graphics		Intel FDI Technology	<b>✓</b>
Discrete graphics card model *	Not available	Intel Fast Memory Access	V
On-board graphics card *	✓	Processor ARK ID	85212
Discrete graphics card *	×	Conflict-Free processor	<b>✓</b>
On-board graphics card model *	Intel® HD Graphics 5500	Power	
On-board graphics card base	300 MHz	AC adapter frequency	50 - 60 Hz
	300 11112		
frequency On-hoard graphics card dynamic		AC adapter input voltage	100 - 240 V
On-board graphics card dynamic frequency (max)	900 MHz	AC adapter input voltage Security	100 - 240 V
On-board graphics card dynamic frequency (max) Maximum on-board graphics card	900 MHz	Security	100 - 240 V
On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory		Security Cable lock slot	<b>√</b>
On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX	900 MHz	Security	100 - 240 V
On-board graphics card dynamic frequency (max) Maximum on-board graphics card memory On-board graphics card DirectX version	900 MHz 16 GB 11.2	Security Cable lock slot Fingerprint reader Password protection	<b>√</b>
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory  On-board graphics card DirectX version  On-board graphics card ID	900 MHz 16 GB	Security Cable lock slot Fingerprint reader Password protection Operational conditions	<i>1 1 1</i>
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio	900 MHz 16 GB 11.2 0x1616	Security Cable lock slot Fingerprint reader Password protection Operational conditions Operating temperature (T-T)	√ √ √ 0 - 35 °C
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip	900 MHz 16 GB 11.2 0x1616  Realtek ALC3235	Security Cable lock slot Fingerprint reader Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T)	√ √ √ 0 - 35 °C -40 - 65 °C
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2	Security Cable lock slot Fingerprint reader Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 35 °C -40 - 65 °C 10 - 90%
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip	900 MHz 16 GB 11.2 0x1616  Realtek ALC3235	Security Cable lock slot Fingerprint reader Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95%
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2	Security  Cable lock slot Fingerprint reader Password protection  Operational conditions  Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	0 - 35 °C -40 - 65 °C 10 - 90%
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers Built-in microphone	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers Built-in microphone  Camera	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2	Security  Cable lock slot Fingerprint reader Password protection  Operational conditions  Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Weight & dimensions	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2	Security  Cable lock slot Fingerprint reader Password protection  Operational conditions  Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude  Weight & dimensions  Width	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio Audio Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2	Security Cable lock slot Fingerprint reader Password protection Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  1280 x 720 pixels	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front)	✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network  Mobile network connection *	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  1280 x 720 pixels	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio Audio Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  /  1280 x 720 pixels	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  /  1280 x 720 pixels  10,100,1000 Mbit/s	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio Audio Audio chip Number of built-in speakers Built-in microphone  Camera Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth  Ports & interfaces	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  1280 x 720 pixels	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  /  1280 x 720 pixels  10,100,1000 Mbit/s	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth  Ports & interfaces  USB 3.2 Gen 1 (3.1 Gen 1) Type-A	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  1280 x 720 pixels	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio Audio Audio chip Number of built-in speakers Built-in microphone  Camera Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth  Ports & interfaces  USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  /  1280 x 720 pixels  X  /  10,100,1000 Mbit/s /	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio Audio Audio chip Number of built-in speakers Built-in microphone  Camera Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth  Ports & interfaces  USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports	900 MHz  16 GB  11.2 0x1616  Realtek ALC3235 2  / 1280 x 720 pixels  X / 10,100,1000 Mbit/s / 3 1	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio Audio Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth  Ports & interfaces  USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports HDMI ports quantity *	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  /  1280 x 720 pixels  X /  10,100,1000 Mbit/s /  1	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm
On-board graphics card dynamic frequency (max)  Maximum on-board graphics card memory On-board graphics card DirectX version On-board graphics card ID  Audio  Audio Audio chip Number of built-in speakers Built-in microphone  Camera  Front camera Front camera resolution  Network  Mobile network connection * Ethernet LAN Ethernet LAN data rates Bluetooth  Ports & interfaces  USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * Ethernet LAN (RJ-45) ports HDMI ports quantity * Mini DisplayPorts quantity	900 MHz  16 GB  11.2  0x1616  Realtek ALC3235 2  1280 x 720 pixels  3 1 1 1 1	Security Cable lock slot Fingerprint reader Password protection  Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude Weight & dimensions Width Depth Height (front) Height (rear)	0 - 35 °C -40 - 65 °C 10 - 90% 5 - 95% 0 - 3048 m 0 - 10668 m 310.5 mm 212.8 mm 2.05 cm 2.27 cm

## Ports & interfaces

USB Sleep-and-Charge 

✓
USB Sleep-and-Charge ports 1



5711603030497

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.