/ISUS

ASUS ProArt PA248QV 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LED Black

Brand : ASUS

Product family: ProArt

Product code: 90LM05K1-B01370

Product name : PA248QV

- 24.1-inch 16:10 WUXGA (1920 x 1200) IPS display with frameless design

- International color standard 100% sRGB and 100% Rec. 709 wide color gamut

- Calman Verified with factory pre-calibrated for excellent color accuracy ($\Delta E < 2$)

- ASUS exclusive ProArt Preset and ProArt Palette provides several adjustable color parameters and preset modes

- Extensive connectivity with DisplayPort, HDMI, D-sub, Audio in, Earphone jack plus four USB 3.0 ports for the most flexibility

- VESA wall-mountable and ergonomic design with tilt, swivel, pivot and height adjustments for a comfortable viewing experience

24.1", 16:10, 1920x1200, IPS, RMS 2x 2W, HDMI, VGA, DP, 3.5mm, 4x USB 3.0, 533x375-505x211 mm, black







Display		Ports & interfaces	
Display diagonal *	61.2 cm (24.1")	HDMI version	1.4
Display resolution *	1920 x 1200 pixels	DisplayPorts quantity	1
HD type *	WUXGA	DisplayPort version	1.2
Native aspect ratio *	16:10	Audio input	1
Display technology *	LED	Headphone out *	1
Panel type *	IPS	Headphone outputs	1
Touchscreen *	×	Headphone connectivity	3.5 mm
Display brightness (typical)	300 cd/m ²	HDCP	1
Response time	5 ms	Ergonomics	
Display surface	Matt	VESA mounting *	1
Screen shape *	Flat	Panel mounting interface	100 x 100 mm
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 720 x 480, 720 x 576, 800 x 600 (SVGA), 832 x 624, 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 768 (WXGA), 1280 x 800 (WXGA), 1280 x 960, 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD	Cable lock slot *	J
		Cable lock slot type	Kensington
		Height adjustment *	✓
		Height adjustment	13 cm
			1
		Pivot angle	-90 - 90°
	1080), 1920 x 1200 (WUXGA)	Swivelling	1
Supported video modes	480p, 576p, 720p, 1080p	Swivel angle range	-90 - 90°
Contrast ratio (typical) *	1000:1	Tilt angle range	-5 - 35°
Contrast ratio (dynamic)	10000000:1	On Screen Display (OSD)	1
Dynamic contrast ratio marketing name	SmartContrast		Simplified Chinese, Traditional
Maximum refresh rate *	75 Hz		Chinese, Croatian, Czech, German, Dutch, English, Spanish, French,
Viewing angle, horizontal	178°	On Screen Display (OSD) languages	Hungarian, Indonesian, Italian,
Viewing angle, vertical	178°		Japanese, Korean, Polish,
Display number of colours *	16.78 million colours		Portuguese, Romanian, Russian, Thai, Turkish
Pixel pitch	0.27 x 0.27 mm	Number of OSD languages	21
Viewable size, horizontal	51.8 cm	LED indicators	1


Display		Ergonomics	
Viewable size, vertical	32.4 cm	Tilt adjustment	4
Viewable size diagonal	61.1 cm	Power	
Digital horizontal frequency	30 - 105 kHz	Energy efficiency class (SDR) *	G
Digital vertical frequency RGB colour space	49 - 75 Hz sRGB	Energy consumption (SDR) per 1000 hours *	28 kWh
sRGB coverage (typical)	100%	Power consumption (typical) *	28.2 W
Performance		Power consumption (standby) *	0.5 W
NVIDIA G-SYNC *	×	Power consumption (off)	0.3 W
AMD FreeSync *	×	AC input voltage	100 - 240 V
VESA Adaptive Sync support	✓	AC input frequency Energy efficiency scale	50/60 Hz A to G
Flicker-free technology			A 10 G
Low Blue Light technology	ý	Operational conditions	
Multimedia		Operating temperature (T-T)	0 - 40 °C -20 - 60 °C
Built-in speaker(s) *	√	Storage temperature (T-T)	-20 - 60 °C
Built-in camera *	2	Packaging content	
Number of speakers RMS rated power	2 4 W	Stand included	V
·	÷ VV	Cables included	AC
Design		Weight & dimensions	
Market positioning *	Graphics design	Width (with stand)	533 mm
Product colour * Frameless design	Black	Depth (with stand)	211 mm
Feet colour	Black	Height (with stand)	505 mm
	UL/cUL, FCC, ICES-3, CB, CE, ErP,	Weight (with stand)	6.1 kg 53.3 cm
	WEEE, TUV-GS, TUV-Ergo, ISO	Width (without stand) Depth (without stand)	4.7 cm
Certification	9241-307, UkrSEPRO, CU, CCC, CEL, BSMI, RCM, MEPS, VCCI, PSE, PC	• •	
		Height (Without Stand)	36 CM
	Recycle, J-MOSS, KC, KCC, e-	Height (without stand) Weight (without stand)	36 cm 3.9 kg
		Weight (without stand)	36 cm 3.9 kg
Ports & interfaces	Recycle, J-MOSS, KC, KCC, e-	Weight (without stand) Packaging data	3.9 kg
Ports & interfaces Built-in USB hub *	Recycle, J-MOSS, KC, KCC, e-	Weight (without stand) Packaging data Package width	3.9 kg 649 mm
Built-in USB hub * USB hub version	Recycle, J-MOSS, KC, KCC, e- Standby, Energy Star 8.0, TCO 3.2 Gen 1 (3.1 Gen 1)	Weight (without stand) Packaging data Package width Package depth	3.9 kg
Built-in USB hub * USB hub version Number of upstream ports	Recycle, J-MOSS, KC, KCC, e- Standby, Energy Star 8.0, TCO	Weight (without stand) Packaging data Package width	3.9 kg 649 mm 192 mm
Built-in USB hub * USB hub version	Recycle, J-MOSS, KC, KCC, e- Standby, Energy Star 8.0, TCO 3.2 Gen 1 (3.1 Gen 1)	Weight (without stand) Packaging data Package width Package depth Package height	3.9 kg 649 mm 192 mm 474 mm
Built-in USB hub * USB hub version Number of upstream ports USB Type-A downstream ports	Recycle, J-MOSS, KC, KCC, e- Standby, Energy Star 8.0, TCO 3.2 Gen 1 (3.1 Gen 1) 1	Weight (without stand) Packaging data Package width Package depth Package height Package weight	3.9 kg 649 mm 192 mm 474 mm
Built-in USB hub * USB hub version Number of upstream ports USB Type-A downstream ports quantity VGA (D-Sub) ports quantity DVI port	Recycle, J-MOSS, KC, KCC, e- Standby, Energy Star 8.0, TCO 3.2 Gen 1 (3.1 Gen 1) 1 4	Weight (without stand) Packaging data Package width Package depth Package height Package weight Sustainability Sustainability certificates	3.9 kg 649 mm 192 mm 474 mm 8.3 kg
Built-in USB hub * USB hub version Number of upstream ports USB Type-A downstream ports quantity VGA (D-Sub) ports quantity	Recycle, J-MOSS, KC, KCC, e- Standby, Energy Star 8.0, TCO 3.2 Gen 1 (3.1 Gen 1) 1 4 1	Weight (without stand) Packaging data Package width Package depth Package height Package weight Sustainability	3.9 kg 649 mm 192 mm 474 mm 8.3 kg











Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.