



## Lindy 150m TosLink & Coaxial Digital Audio Extender

**Brand :** Lindy

**Product code:** 70456

**Product name :** 150m TosLink & Coaxial Digital Audio Extender

- Extends TosLink (Optical) & coaxial digital audio up to 150m over network cable
- Supports stereo and multi-channel audio formats including Dolby Digital & DTS
- Supports PoC (Power over Cat Cable) from the transmitter to receiver
- Simultaneous audio output

150m Cat.6 TosLink (Optical) & Coaxial Digital Audio Extender

Lindy 150m TosLink & Coaxial Digital Audio Extender. Type: AV transmitter & receiver, Cable types supported: Cat5e, Cat6, Maximum transfer distance: 150 m. Connectivity technology: Wired, Digital audio optical input type: TOSLINK. Operating voltage (transmitter): 12 V, Current: 1.25 A. Receiver dimensions (WxDxH): 65.9 x 26.9 x 53.1 mm, Receiver weight: 168 g, Transmitter dimensions (WxDxH): 65.9 x 26.9 x 53.1 mm. Package width: 190 mm, Package depth: 60 mm, Package height: 145 mm



Features		Power	
Type *	AV transmitter & receiver	Current	1.25 A
Cable types supported	Cat5e, Cat6	<b>Operational conditions</b>	
Maximum transfer distance	150 m	Operating temperature (T-T)	0 - 50 °C
Chipset	EL5171/ EL5172	Storage temperature (T-T)	-10 - 80 °C
Audio formats supported	DTS, LPCM	Operating relative humidity (H-H)	5 - 90%
Material	Metal	<b>Weight &amp; dimensions</b>	
Product colour	Black	Receiver dimensions (WxDxH)	65.9 x 26.9 x 53.1 mm
Certification	CE, FCC, RoHS, REACH & California Proposition 65	Receiver weight	168 g
<b>Ports &amp; interfaces</b>		Transmitter dimensions (WxDxH)	65.9 x 26.9 x 53.1 mm
Connectivity technology *	Wired	Transmitter weight	168 g
RJ-45 input ports	1	<b>Packaging data</b>	
RJ-45 output ports	1	Package width	190 mm
Digital audio coaxial in	1	Package depth	60 mm
Digital audio coaxial out	1	Package height	145 mm
Digital audio optical in	1	Package weight	405 g
Digital audio optical input type	TOSLINK	Package type	Box
Digital audio optical out	1	<b>Packaging content</b>	
DC-in jack	✓	AC adapter included	✓
<b>Power</b>		Included power plug types	EU, UK, US
Operating voltage (transmitter)	12 V	Manual	✓
<b>Technical details</b>			
Sustainability certificates		RoHS	



4002888704564

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 17-JAN-2023. Prints or copies of Information are only valid on the printed Publication date