



## TP-Link OC200 gateway/controller 10, 100 Mbit/s

**Brand :** TP-Link

**Product code:** OC200

**Product name :** OC200

- Omada Wi-Fi network controller
- Accessible through direct access, cloud portal or mobile app
- Pre-installed Omada controller software. Power it on and start to play
- No license fee, no monthly fee, manage from anywhere, anytime
- Dual power selection PoE (802.3af/802.3at) and micro USB flexible installations
- Powerful CPU and USB auto backup for robustness and stability
- Secure guest network with multiple login options(Facebook Wi-Fi, SMS login, Voucher)

10/100Mbps LAN, USB 2.0, Micro USB, PoE, 100x98x25 mm

TP-Link OC200. Certification: CE, FCC, RoHS. Processor frequency: 1000 MHz, Internal memory: 1024 MB, Internal memory type: DDR3. Ethernet LAN data rates: 10,100 Mbit/s, Networking standards: IEEE 802.3af, IEEE 802.3at. Security algorithms: SSID, WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Management platform: L3



<b>Design</b>		<b>Management features</b>	
LED indicators	✓	Quality of Service (QoS) support	✓
Certification	CE, FCC, RoHS	Reset button	✓
<b>Performance</b>		<b>Power</b>	
Control display unit *	✗	Power consumption (typical)	5 W
Built-in processor	✓	Power over Ethernet (PoE)	✓
Processor frequency	1000 MHz	DC input voltage	5 V
Number of processors installed	1	<b>Software</b>	
Internal memory	1024 MB	Compatible operating systems	Windows10, 8, 7,Vista, XP; MAC OS; NetWare, UNIX; Linux
Internal memory type	DDR3	<b>Weight &amp; dimensions</b>	
Flash memory	4000 MB	Width	100 mm
<b>Network</b>		Depth	98 mm
Ethernet LAN data rates	10,100 Mbit/s	Height	25 mm
Networking standards	IEEE 802.3af, IEEE 802.3at	<b>Packaging content</b>	
<b>Security</b>		Cables included	LAN (RJ-45)
MAC address filtering	✓	Quick installation guide	✓
Security algorithms	SSID, WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	<b>Operational conditions</b>	
VLAN support	✓	Operating temperature (T-T)	0 - 40 °C
<b>Ports &amp; interfaces</b>		Storage temperature (T-T)	-40 - 70 °C
USB 2.0 ports quantity	1	Operating relative humidity (H-H)	10 - 90%
Ethernet LAN (RJ-45) ports	2	Storage relative humidity (H-H)	5 - 90%
<b>Management features</b>		<b>Logistics data</b>	
Management platform	L3	Harmonized System (HS) code	85176990
Web-based management	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 20-JAN-2023. Prints or copies of Information are only valid on the printed Publication date