ASUS BE24EQSB computer monitor $60.5 \text{ cm} (23.8") 1920 \times 1080$ pixels Full HD LED Black

Brand : ASUS Product code: BE24EQSB

Product name: BE24EQSB

- 23.8-inch Full HD(1920x1080) frameless IPS panel with wide viewing angles
- Extensive connectivity with DisplayPort, HDMI, D-sub, Audio in, Earphone jack plus four USB 3.0 ports for the most flexibility
- Ergonomic design with $\pm 35^\circ \sim -5^\circ$ tilt, $\pm 180^\circ$ swivel, $\pm 90^\circ$ pivot and 130mm height adjustments for a comfortable viewing experience
- TÜV Rheinland Certification for Flicker-free and Low Blue Light technology to ensure a comfortable viewing experience

23.8", 16:9, 1920x1080, IPS, RMS 2x 2W, HDMI, 3.5mm, DP, USB 3.0, 540x332-462x211mm, black ASUS BE24EQSB. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black







Display		Ports & interfaces	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type *	60.5 cm (23.8") 1920 x 1080 pixels Full HD 16:10 LED IPS	Audio input Headphone out * Headphone outputs Headphone connectivity HDCP AC (power) in	✓ ✓ 1 3.5 mm ✓
Touchscreen *	×	Ergonomics	•
Display brightness (typical) Response time Screen shape * Supported graphics resolutions	300 cd/m ² 5 ms Flat 640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 832 x 624, 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1280 x 960, 1366 x 768, 1440 x 900 (WXGA+), 1680 x 1050 (WSXGA+), 1920 x 1080 (HD 1080)	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Pivot angle	✓ 100 x 100 mm ✓ Kensington ✓ 13 cm ✓ -90 - 90°
Supported video modes	480p, 576p, 720p, 1080p	Swivelling	✓
Contrast ratio (typical) *	1000:1	Swivel angle range	-180 - 180°
Contrast ratio (dynamic)	100000000:1	Tilt angle range	-5 - 35°
Maximum refresh rate *	60 Hz	On Screen Display (OSD)	✓
Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Viewable size, horizontal	178° 178° 16.78 million colours 0.275 x 0.275 mm 52.7 cm	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, French, Hungarian, Indonesian, Italian, Japanese, Korean, Polish, Portuguese, Romanian, Russian, Thai, Turkish
Viewable size, vertical	29.6 cm	Number of OSD languages	21
Viewable size diagonal	60.5 cm	LED indicators	Power, Stand-by
Digital horizontal frequency	55 - 96 kHz 48 - 77 Hz	Tilt adjustment	✓
Digital vertical frequency NTSC coverage (typical)	72%	Power	
		Energy efficiency class (SDR) *	D

Performance		Power	
NVIDIA G-SYNC * AMD FreeSync *	×	Energy consumption (SDR) per 1000 hours *	14 kWh
Flicker-free technology	7	Power consumption (typical) *	15 W
Low Blue Light technology	1	Power consumption (standby) *	0.5 W
Multimedia	•	Power consumption (PowerSave)	0.5 W
	,	AC input voltage	100 - 240 V
Built-in speaker(s) *	√	AC input frequency	50/60 Hz
Built-in camera * Number of speakers	2	Energy efficiency scale	A to G
RMS rated power	4 W	Operational conditions	
	4 VV	Operating temperature (T-T)	0 - 40 °C
Design		Storage temperature (T-T)	-20 - 60 °C
Market positioning *	Business	Packaging content	
Product colour *	Black	Stand included	√
Frameless design	✓	Cables included	AC, USB
Front bezel colour	Black		АС, ОЗВ
Feet colour	Black	Weight & dimensions	
	Energy Star, BSMI, CB, CCC, CE, CEL level, CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSE, RoHS, TUV-Ergo, TUV-GS, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 8, Windows 7), RCM, TUV	Width (with stand)	540 mm
		Depth (with stand)	211 mm
Cartification		Height (with stand)	332 mm
Certification		Weight (with stand)	7.8 kg
	Flicker-free , KC , eStandby, TUV	Width (without stand)	54 cm
	Low Blue Light, TCO, ICES-3, PC recycle	Depth (without stand)	4.7 cm
	recycle	Height (without stand)	33 cm
Ports & interfaces		Weight (without stand)	5 kg
Built-in USB hub *	✓	Packaging data	
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package width	849 mm
USB upstream port type	USB Type-B	Package depth	192 mm
USB Type-A downstream ports	4	Package height	474 mm
quantity	1	Package weight	10.5 kg
VGA (D-Sub) ports quantity DVI port	×	Sustainability	
HDMI *	^	Sustainability certificates	RoHS, ENERGY STAR
HDMI ports quantity	1	·	NOTIS, ENERGY STAIN
HDMI version	1.4	Logistics data	
DisplayPorts quantity	1	Harmonized System (HS) code	85285210
DisplayPort version	1.2		

