EPSON
EXCEED YOUR VISION

Epson TM-M30II 203 x 203 DPI Wired & Wireless Direct thermal POS printer

Brand : Epson

Product name : TM-M30II

Product code: C31CJ27111A0

- Iconic design: Stylish, practical design with small footprint and clean lines
- Cost effective: Entry-level model (refreshed version of its predecessor, the TM-m30)
- Fast printing: Increased print speed of 250mm/s
- Direct printing from mobile devices: Without the need to install or update drivers
- Reliable: Epson's tried and trusted build quality

Compact mPOS receipt printer TM-M30II (111A0): USB + ETHERNET + BT, WHITE, PS, UK
Epson TM-M30II. Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite), Maximum printing width: 8 cm. Connectivity technology: Wired & Wireless, USB connector: USB Type-A / USB Type-B. Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h, Autocutter durability: 1.5 million cuts. Product colour: White

Printing

Maximum resolution	203 x 203 DPI
Print speed	250 mm/sec
Print speed (receipt)	250 mm/sec
Printing characters	Text, Graphic, Barcode
Character sets	ANK
Print technology *	Direct thermal
Type *	POS printer

Paper handling

Maximum roll diameter	8.3 cm
Supported paper width	58 mm - 80 mm (Breite)
Maximum printing width	8 cm

Ports & interfaces

USB port *	✔
USB 2.0 ports quantity	2
USB connector	USB Type-A / USB Type-B
Bluetooth	✔
Connectivity technology *	Wired & Wireless
Near Field Communication (NFC)	✔

Network

Ethernet LAN *	✔
Wi-Fi *	✘

Features

Sound pressure level (printing)	55 dB
Mean time between failures (MTBF)	360000 h
Half-cutter	✔
Autocutter durability	1.5 million cuts
Print head life	150 km
Country of origin	Philippines
Mounting position	Horizontal/Vertical
Wall mountable	✔

Operational conditions

Operating temperature (T-T)	5 - 45 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

System requirements

Pre-installed software	TMNet WebConfig, ePOS-Device, ePOS-Display, ePOS-Print

Weight & dimensions

Width	127 mm
Depth	127 mm
Height	127 mm
Weight	1.3 kg

Packaging data

Quantity per pack	1 pc(s)
Package width	193 mm
Package depth	235 mm
Package height	233 mm
Package weight	2.2 kg

Packaging content

AC adapter included	✔

Print technology

Column capacity	48/57

Logistics data

Products per master (outer) case	4 pc(s)
Master (outer) case width	400 mm
Master (outer) case length	490 mm
Master (outer) case height	255 mm
Products per pallet	128 pc(s)
Products per pallet (UK)	192 pc(s)

Features

Built-in sensors details	Paper End Sensor, Paper Near End Sensor, Papier-Sensor

Design

Product colour *	White

Power

Power source type *	AC
Power plug type	Type G

Technical details

Font styles	ANK
Lifetime	17000000 lines
Harmonized System (HS) code	84433210

Other features

Buffer size	12 KB
Mean cycles between failures (MCBF)	65000000
Print head life	150.000.000 Impulse

8715946688527