

DELL S Series S3221QS 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD LCD Silver

Brand : DELL

Product family: S Series

Product code: DELL-S3221QS

Product name : S3221QS

- 81.3cm (32") 4K Ultra HD 3840 x 2160 LED VA
- 4ms, 16:9, 300cd/m², 3000:1
- USB, HDMI, DisplayPort
81.3cm (32") 4K Ultra HD 3840 x 2160 LED VA, 16:9, 300cd/m², 1.073B, 4ms, 3000:1

DELL S Series S3221QS 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD LCD Silver:

31.5" curved 4K UHD monitor that supports HDR content playback for a truly immersive entertainment experience.

DELL S Series S3221QS. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Silver







Display		Network	
Display diagonal *	80 cm (31.5")	Wi-Fi	×
Display resolution *	3840 x 2160 pixels	Ergonomics	
HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen * Display brightness (typical) Response time Screen shape * Supported graphics resolutions Supported video modes	4K Ultra HD 16:9 LCD VA LED X 300 cd/m ² 4 ms Curved 3840 x 2160 480i, 480p, 576i, 576p, 720p, 1080i, 1090a, 3840a	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Pivot Swivelling Tilt angle range Picture-in-Picture Tilt adjustment	<pre> / 100 x 100 mm / Kensington / 7 cm X -5 - 21° / / </pre>
Aspect ratio	1080p, 3840p 16:9	Power	
Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast) Pixel pitch Pixel density	3000:1 60 Hz 178° 178° 1.073 billion colours 5 ms 0.18159 x 0.18159 mm 139 ppi	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Energy consumption (HDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) * Power consumption (max)	G G 39 kWh 56 kWh 38.5 W 0.2 W 91 W
Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical High Dynamic Range (HDR) supported RGB colour space	29 - 170 kHz 40 - 60 Hz 69.7 cm 39.2 cm ✓ sRGB	Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type Energy efficiency scale	91 W 0.2 W 100 - 230 V 50/60 Hz 1.6 A Internal A to G

Display		Power	
sRGB coverage (typical)	99%	Annual energy consumption	57 kWh
Performance		Operational conditions	
AMD FreeSync * AMD FreeSync refresh rate range Flicker-free technology Low Blue Light technology	✓ 40 - 60 Hz ✓	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -20 - 60 °C 10 - 80% 10 - 90%
Multimedia		Operating altitude	0 - 5000 m
Built-in speaker(s) *	1	Non-operating altitude	0 - 12192 m
Built-in camera * Number of speakers RMS rated power	× 2 10 W	Packaging content Stand included Cables included	✔ AC, HDMI, USB
Design		Weight & dimensions	
Market positioning * Product colour * Front bezel colour Detachable stand Feet colour Heavy metals free Country of origin Ports & interfaces Built-in USB hub *	Business Silver Black Silver Hg (mercury) China	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand) Bezel width (side)	709.2 mm 207 mm 518.1 mm 10.5 kg 70.9 cm 6.4 cm 42.5 cm 7.4 kg 8.2 mm
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Bezel width (top) Bezel width (bottom)	8.1 mm 2.44 cm
USB upstream port type Number of upstream ports	USB Type-B 1	Packaging data	
USB Type-A downstream ports quantity USB Power Delivery DVI port	3 Type-A downstream ports 2 antity 2 3 Power Delivery ✓ I port ×	Package width Package depth Package height Package weight	172 mm 939.8 mm 525 mm 15.2 kg
HDMI *	√ 2	Sustainability	
HDMI ports quantity DisplayPorts quantity	2	Sustainability certificates	RoHS
DisplayPort version	1.2	Logistics data	
Audio input Audio output	× √	Commodity Classification Automated Tracking System	85285931
Headphone out *	×	(CCATS) Harmonized System (HS) code	85285210



5397184409442

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.