ZYXEL

Zyxel GS1900-24EP Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Brand: Zyxel **Product code**: GS1900-24EP-GB0101F

Product name: GS1900-24EP

24-port GbE Smart Managed PoE Switch

Zyxel GS1900-24EP. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Full duplex. MAC address table: 8000 entries, Switching capacity: 48 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1ab, IEEE 802.1af, IEEE 802.1s, IEEE 802.1w, IEEE 802.3at, IEEE 802.3az,.... Power connector: AC-in jack. Power over Ethernet (PoE). Rack mounting





Management features		Security	
Switch type * Switch layer Quality of Service (QoS) support MIB support	Managed L2 ✓ RFC 1213 MIB II RFC 2819 RMON (group 1, 2, 3, 9) RFC 1215 generic traps RFC 1493 bridge Zyxel private common MIB	Security algorithms MAC address filtering Static port security SSH/SSL support Password protection Authentication type	802.1x RADIUS
Ports & interfaces		Multicast features	
Basic switching RJ-45 Ethernet ports	24	Multicast support	✓
quantity *		Design	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Rack mounting *	✓
Power connector	AC-in jack	Stackable *	✓
Network		Product colour	Black
	IEEE 802.1D, IEEE 802.1ab, IEEE	Reset button	✓
Notworking standards *	802.1af, IEEE 802.1s, IEEE 802.1w, IEEE 802.3at, IEEE 802.3az, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x	Performance	
Networking standards *		Noise level	26 dB
10G support *	×	Power	
Cable types supported	Cat5, Cat5e	Power source *	AC
Port mirroring	✓	Power supply included *	✓
Full duplex	✓	AC input voltage	100 - 240 V
Flow control support	✓	AC input frequency	50/60 Hz
Link aggregation	✓	Power consumption (max)	166.5 W
Auto MDI/MDI-X	✓	Power over Ethernet (PoE)	
Spanning tree protocol	×	Power over Ethernet (PoE) *	1
Ethernet LAN data rates	10,100,1000 Mbit/s	Power over Ethernet (PoE) ports	10
MAC address auto-learning supported	✓	quantity	12
VLAN support	✓	Total Power over Ethernet (PoE) budget	130 W
Virtual LAN features	Tagged VLAN, VLAN Identifier (VLAN ID), Voice VLAN	Weight & dimensions	
Data transmission		Width	330 mm
Switching capacity *	48 Gbit/s	Depth	230 mm

Data transmission		Weight & dimensions	
Forwarding rate 35.7 Mpps MAC address table * 8000 entries	Height Weight	44 mm 2.48 kg	
Store-and-forward Jumbo frames support	•	Packaging data	
umbo frames 9000	Cables included Quick start guide	AC 🗸	
Packet buffer memory	0.525 MB	User guide	√ ·
Security		Manual	✓
DHCP features IGMP snooping	DHCP client ✓		

