## **PHILIPS**

## Philips B Line 275B1 computer monitor 68.6 cm (27") 2560 x 1440 pixels 2K Ultra HD LCD Black

Brand : Philips Product family: B Line Product code: 275B1

**Product name:** 275B1

- B Line
- 27" (68.6 cm)
- 2560 x 1440 (QHD)

IPS, LCD, W-LED, 27",  $596.736 \times 335.664$ , 16:9,  $2560 \times 1440 @ 75Hz$ , 109 PPI, 4 ms, 300 cd/m² Philips B Line 275B1. Display diagonal: 68.6 cm (27"), Display resolution:  $2560 \times 1440$  pixels, HD type: 2K Ultra HD, Display technology: LCD, Display surface: Matt, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal:  $178^\circ$ , Viewing angle, vertical:  $178^\circ$ . Built-in speaker(s). Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black





Display		Ports & interfaces	
Display diagonal * Display resolution * HD type * Native aspect ratio * Display technology * Panel type * Backlight type Touchscreen *	68.6 cm (27") 2560 x 1440 pixels 2K Ultra HD 16:9 LCD IPS W-LED	HDMI * HDMI ports quantity HDMI version DisplayPorts quantity DisplayPort version Audio output HDCP DC-in jack	1 1.4 1 1.2 1
Display brightness (typical)	300 cd/m <sup>2</sup>	Ergonomics	
Response time	4 ms		4
Display surface	Matt	VESA mounting *	100 × 100 mm
Screen shape *	Flat	Panel mounting interface	100 x 100 mm
Supported graphics resolutions	1280 x 720 (HD 720), 1360 x 768 (WXGA), 1920 x 1200 (WUXGA), 2560 x 1440	Cable lock slot * Cable lock slot type Height adjustment *	✓ Kensington
Supported video modes	720p, 768p, 1080p, 1440p	Height adjustment	15 cm
Aspect ratio	16:9	Pivot	✓
Contrast ratio (typical) *	1000:1	Pivot angle	90 - 90°
Contrast ratio (dynamic)	50000000:1	Swivelling	✓
Dynamic contrast ratio marketing	SmartContrast	Swivel angle range	0 - 180°
name Maximum refresh rate *	75 Hz	Tilt angle range	-5 - 35°
	178°	On Screen Display (OSD)	✓
Viewing angle, horizontal Viewing angle, vertical Display number of colours * Pixel pitch Pixel density	178° 16.78 million colours 0.2331 x 0.2331 mm 109 ppi	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Horizontal scan range	30 - 114 kHz	Number of OSD languages	21
Vertical scan range	48 - 75 Hz	Plug and Play	✓
Viewable size, horizontal	59.7 cm	LED indicators	Operation, Stand-by
Viewable size, vertical	33.6 cm	Tilt adjustment	✓
Digital horizontal frequency	30 - 114 kHz	Power	
Digital vertical frequency	48 - 75 Hz	Energy efficiency class (SDR) *	F
RGB colour space Colour gamut	sRGB 110%	Energy consumption (SDR) per 1000	
sRGB coverage (typical)	123%	hours *	
NTSC coverage (typical)	110%	Power consumption (typical) *	18 W
	11070	Power consumption (standby) *	0.4 W
Performance		Power consumption (PowerSave)	17.5 W
NVIDIA G-SYNC *	×	AC input voltage	100 - 240 V
AMD FreeSync *	×	AC input frequency	50/60 Hz
VESA Adaptive Sync support	✓	Energy efficiency scale	A to G
Component video sync	Separate sync		

Performance		Operational conditions	
Flicker-free technology Low Blue Light technology	<b>✓</b>	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 60 °C
Multimedia		Operating relative humidity (H-H)	20 - 80%
Built-in speaker(s) * Built-in camera * Number of speakers	<b>✓ ×</b> 2	Storage relative humidity (H-H) Operating altitude Non-operating altitude	20 - 80% 0 - 3658 m 0 - 12192 m
RMS rated power	2 W	Packaging content	
Design		Stand included	✓
Market positioning *	Business	Weight & dimensions	
Product colour * Frameless design Front bezel colour Detachable stand Feet colour  Certification	Black  Black  Black  CB, EPA, FCC Class B, ICES-003, CE Mark, TUV Ergo, TUV/GS, SEMKO, CU-EAC, UKRAINIAN, TUV Eye	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand) Weight (without stand)	613 mm 205 mm 537 mm 6.36 kg 61.3 cm 5.1 cm 36.6 cm 4.75 kg
Ports & interfaces		Packaging data	
Built-in USB hub * USB hub version USB upstream port type Number of upstream ports USB Type-A downstream ports quantity	✓ 2.0 / 3.2 Gen 1 (3.1 Gen 1) USB Type-B 1	Package width Package depth Package height Package weight Package type	700 mm 216 mm 456 mm 8.47 kg Box
DVI port	✓	Sustainability	
DVI-D ports quantity	1	Sustainability certificates	RoHS, ENERGY STAR





609585253865

0609585253865

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.