Benq MX536 data projector Standard throw projector 4000 ANSI lumens DLP XGA (1024x768) White

Brand : Benq

Product name : MX536

Product code: 9H.JN777.33E

- 4000 ANSI Lumen High brightness and 20,000:1 High Contrast
- Exclusive Data Review Mode Showcases Text and Charts in Detail
- Powered USB port for charging your devices

DLP Single 0.55" XGA, 1024 x 768 pixels, 1080p, 4000 ANSI, 20.000 : 1

Benq MX536. Projector brightness: 4000 ANSI lumens, Projection technology: DLP, Projector native resolution: XGA (1024x768). Light source type: Lamp, Service life of light source: 5500 h, Service life of light source (economic mode): 20000 h. Focus: Auto/Manual, Zoom ratio: 1.2:1, Throw ratio: 1.942~2.332. Analog signal format system: NTSC, PAL, SECAM, Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, Video colour modes: Presentation, sRGB. Serial interface type: RS-232

Projector

Screen size compatibility *	1524 - 3810 mm (60 - 150")
Projector brightness *	4000 ANSI lumens
Projection technology *	DLP
Projector native resolution *	XGA (1024x768)
Contrast ratio (typical) *	20000:1
Native aspect ratio *	4:3
Horizontal scan range	15 - 102 kHz
Vertical scan range	23 - 120 Hz
Keystone correction, vertical	-40 - 40°

Light source

Light source type *	Lamp
Service life of light source *	5500 h
Service life of light source (economic mode)	20000 h
Lamps quantity	1 lamp(s)

Lens system

Focus *	Auto/Manual
Zoom capability	✔
Zoom ratio	1.2:1
Throw ratio	1.942~2.332
Offset	106%

Video

Analog signal format system *	NTSC, PAL, SECAM
Full HD *	✖
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video colour modes	Presentation, sRGB

Ports & interfaces

S-Video inputs quantity	1
USB 2.0 ports quantity *	2
Mini-USB 2.0 ports quantity	1

Features

Noise level (economic mode)	29 dB
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese
Number of OSD languages	30
Noise level *	32 dB

Multimedia

Built-in speaker(s) *	✔
RMS rated power	2 W
Number of built-in speakers	1

Design

Market positioning *	Presentation
Product type *	Standard throw projector
Product colour *	White
Placement	Ceiling, Desktop
LED indicators	✔
Cable lock slot	✔
Cable lock slot type	Kensington

Power

Power source *	AC
Power consumption (typical) *	240 W
Power consumption (standby) *	0.5 W
Power consumption (max)	260 W
Power consumption (economy mode)	190 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz

Ports & interfaces

Serial interface type *	RS-232
PC Audio in	✔
PC Audio out	✔
VGA (D-Sub) ports quantity *	3
HDMI ports quantity *	2
Composite video in *	1
DVI port *	✘
AC (power) in	✔

Network

Smart TV *	✘
Ethernet LAN *	✘
Wi-Fi *	✘

Storage

Card reader integrated *	✘

Power

Auto power off	✔

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	332 mm
Depth	241 mm
Height	101 mm
Weight *	2.6 kg

Packaging content

Remote control included *	✔
Remote control type	IR
Cables included	AC, VGA
Manual	✔

Logistics data

Quantity per pack	1 pc(s)
Harmonized System (HS) code	85286200

4718755084089

0840046044503

840046044503